


Kiowa Co)

19W 271

1 LOCATION OF WATER WELL: County: Osage Osage	Fraction C $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 13	Township Number T 29 S	Range Number R 32N EW
--------------------------------------------------------------------	---------------------------------------------------------------	----------------------	---------------------------	--------------------------------------------

Distance and direction from nearest town or city street address of well if located within city?
5 S, 3 W of Greensburg, Kansas

2 WATER WELL OWNER: Calvin Unruh RR#, St. Address, Box #: Route 1 City, State, ZIP Code: Greensburg, Ks. 67504	H-30 Drilling, Inc. Unruh-Gray #6 251 N. Water, Suite 10 Wichita, Ks. 67202 Application Number: T87-205
----------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 233 ft. ELEVATION: 180
	Depth(s) Groundwater Encountered: 1. 180 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 180 ft. below land surface measured on mo/day/yr 5/2/87 Pump test data: Well water was 60 ft. after hours pumping gpm Est. Yield: 8 gpm Well water was 233 ft. after hours pumping gpm Bore Hole Diameter: 8 in. to 233 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded
Blank casing diameter: 5 in. to 213 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 213 ft. to 233 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 10 ft. to 233 ft., From ft. to ft.	

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage	
Direction from well? South How many feet? 60	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	180	Clay			
180	233	Sand and gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/2/87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 6/14/87 under the business name of Kelly's Water Well Service by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
29
R
19
END
SEC. 13
NW 1/4
NW 1/4
SE 1/4