

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: SW 1/4 SW 1/4 NW 1/4 Section Number: 6 Township Number: T 29 S Range Number: R 2 E W

Distance and direction from nearest town or city street address of well if located within city? See below

2 WATER WELL OWNER: Marla McElhaneey RR#, St. Address, Box #: 7424 S. 21st W. City, State, ZIP Code: Viola, KS 67149 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NW corner]

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 1-2-97 ft. 3. ft. 4. ft. WELL'S STATIC WATER LEVEL: 13 ft. below land surface measured on mo/day/yr Pump test data: Well water was 10-15 gpm. Well water was 11 in. to 80 ft. and 80 in. to 80 ft. Bore Hole Diameter: 11 in. to 80 ft. and 80 in. to 80 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter 5 in. to 20 ft. Dia 2.40 in. to 2.40 in. Dia 160 PSI Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160 PSI TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20 ft. to 80 ft. From 13 ft. to 80 ft. GRAVEL PACK INTERVALS: From 13 ft. to 80 ft. From 13 ft. to 80 ft.

6 GROUT MATERIAL: 3 Neat cement 13 Cement grout 3 Bentonite 4 Other Grout intervals: From 13 ft. to 13 ft. From 13 ft. to 13 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage How many feet? 150 ft.

Direction from well? South west

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 18 clay

18 80 green & charcoal shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-2-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 312 This Water Well Record was completed on (mo/day/yr) 1-2-97 under the business name of Weneringer Drilling & Inc. by (signature) Michele Baker

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.