1 LOCATIO	ON OF WATER WELL:	FRACTION	Water Well Re	cord Form WWC-5		T		
		SW 1/4	SW 1/4	3.17 47 1/4	Section Number	Township Number	Range Number	
Distance and direction frem nearest town or city street address of well if				NW 1/4	24	т 29 s	R = 2W E/W	
640 N. 4th Clearwater, Kansas								
WATER WELLOWNER: UNITED STATES POST OFFICE								
RR#, ST. ADRESS, BOX#: 640 N. 4th Board of Agriculture, Divivsion of Water Resource								
CITY, ST.	ATE, ZIP CODE: Cle	arwater, Ka				Application Number	er:	
	WELL'S LOCATION WITH SECTION BOX:	DEPTH OF COM	APLETED WELI	L 114	ft. ELE	VATION:		
,	N N	Depth(s) groundw		-	ft.	2 ft.	3 ft.	
		WELL'S STATIC W			BELOW LAND SUR	RFACE MEASURED ON mo/day/yr	07/28/1999	
'	NWNE	Pump test Est. Yield		ll water was		after hours pum	. o br	
W K		Bore Hole Diameter	gpm: Wei	ll water was to 114		after hours pum	BI	
ĭ ≅ w i	r l	WELL WATER TO E		5 Public water	ft. r supply s	and in. 8 Air conditioning 11 I	to ft. Injection well	
		1 Domestic	3 Feedlot	6 Oil fleid wa			injection well Other (Specify below)	
	*** T	2 Irrigation	4 Industrial	7 Lawn and g		0 Monitoring well	when the second	
↓ ∟	S	Was a chemical/bacte	riological sample	submitted to De	partment? Yes	No X; If yes, n	no/day/yr sample was	
a Taylor		submitted			Wate	er Well Disinfected? Yes	X No	
5 TYPE	OF CASING USED:		5 Wrought iron		Concrete tile		Glued X Clamped	
2 PVC	3 RMP (SR)		6 Asbestos-Cement 9 Other (Specify below) Welded					
	4 ABS g Diameter 5	L 4- 30	7 Flberglass		DR-26		Threaded	
	Ī., T	in. to 30	ft., Dia	in. 2.35	to	ft., Dia in.	to ft.	
	SCREEN OR PERFORAT		weight		lbs. / ft. V PVC	Wall thickness or gauge No. 10 Asbestos-ceme	.214 ent	
1 Steel	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify		
2 Brass	4 Galvanized stee		6 Concrete tile	9	ABS	12 None used (or	•	
1	OR PERFORATION OPE	ENING ARE:	5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous	5 William		6 Wire wrapped			9 Drilled holes		
2 Louvered	, F		7 Tor	rch cut		10 Other (specify)		
SCREEN-PI	ERFORATION INTERV	ALS: from 30	!	ft. to 114	ft., From	ft. to	ft.	
from			ft. to		ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from					ft., From	14 40	ft.	
from ft. to ft., From ft. to GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hent on it e hole n							t.	
Grout Intervals: From 4 ft. to 24			ft. From ft. to			4 Other bentonite hole plug ft. From 24 ft. to 26 ft.		
What is the nearest source of possible contamination:						0 Livestock pens 24 n. to 25 n. 14 Abandon water well		
1 Septic tank 4 Lateral lines		al lines	7 Pit privy		11 Fuel stor	rage 15 C	Dil well/Gas well	
2 Sewer lines 5 Cess pool						Fertilizer storage 16 Other (specify below) Insecticide storage		
_	ht sewer lines 6 Seepa	.	9 Feedyard		13 Insectici	•		
Direction fro		est LITHOLOGIC LOG	FROM TO		How many feet? 100			
0 3	topsoil	MINOLOGIC LOC		FRON	ТО	PLUGGING INTER	RVALS	
3 12	2 clay							
12 11	14 grey sha	le					70.00	
ļ <u>.</u>					T			
					 			
					 		· · · · · · · · · · · · · · · · · · ·	
					 			
					1			
					<u> </u>			
					<u> </u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
							1 1 1 3 1 9	