

1 LOCATION OF WATER WELL: Fraction: Section Number: Township Number: Range Number:
County: Sedgwick SW 1/4 SE 1/4 7 T 29 S R 2 E
Distance and direction from nearest town or city street address of well if located within city? 20800 W. 87th S.

2 WATER WELL OWNER: Dan Creswell
RR#, St. Address, Box #: 2620 S. 3831st W.
City, State, ZIP Code: Cheney, KS 66705
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION: 7-301
Depth(s) Groundwater Encountered: 10 ft.
WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 25 gpm. Well water was 34 ft. after hours pumping gpm
Est. Yield: 25 gpm. Well water was 34 ft. after hours pumping gpm
Bore Hole Diameter: 11 in. to 34 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter: 12 in. to 26 ft. Dia. 2.40 in. to ft. Dia. in. lbs./ft. Wall thickness or gauge No. 160 psi
Casing height above land surface: 12 in., weight 2.40 lbs./ft.
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 26 ft. to 34 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 12 ft. to 34 ft. From ft. to ft.
6 GROUT MATERIAL:
1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 10 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? north How many feet? 150

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 34 sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-301 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-27-01
under the business name of Weninger Drilling Inc. by (signature) Michelle Gorge

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRINT FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.