

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Seaport</u>	<u>NW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>10</u>	T <u>29</u> S <u>10</u>	R <u>2</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>16 mi S E 16 mi W</u>				

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

		N	
		X	
W	---	---	E
		S	

4) DEPTH OF COMPLETED WELL ft. ELEVATION: ft.

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 9-2004

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 1.2 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		7 Domestic (lawn & garden)	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:		3 Wrought iron		8 Concrete tile		CASING JOINTS: Glued ☒ Clamped ☐	
1 Steel	5 3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)			Welded ☐	
2 PVC	4 ABS	7 Fiberglass					Threaded ☐
Blank casing diameter 5 in. to 10 ft., Dia		12 240 in. to 160 ft., Dia					
Casing height above land surface 12 in., weight				lbs./ft. Wall thickness or gauge No. 160			
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC	10 Asbestos-Cement			
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)			
			9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:				5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes				
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	ft.			
SCREEN-PERFORATED INTERVALS:				From 10 ft. to 80 ft.	From	ft. to	ft.
				From	ft. to	ft.	ft.
GRAVEL PACK INTERVALS:				From 15 ft. to 80 ft.	From	ft. to	ft.
				From	ft. to	ft.	ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 15 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? opentfield
How many feet?

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No This Water Well Record was completed on (mo/day/yr) under the business name of by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.