WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick \mathbf{SW} 1/4 NE NW25 Т 29 s R 2W E/W 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 1112 Park Glen Clearwater, Kansas WEAVER VENTURES LLC WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#.ST. ADDRESS.BOX #: 1018 W. 8th ZIP CODE: 67152 Wellington, Kansas CITY, STATE: Application Number: 4 DEPTH OF COMPLETED WELL: 70 ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: NW Pump test data: Well water was ft. after hours of pumping @ NE: apm Est. Yield: Well water was hours of pumping @ apm ft. after gpm Ē₩ to 70 12 Bore Hole Diameter and WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 1. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 6. Oil field water supply 8. Air conditioning 4. Industrial Was a chemical/bacteriological sample submitted to Department? ; If yes, what mo/day/yr was sample (NO s Was Water Well Disinfected? submitted YES NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 38 ft., Dia. ft., Dia. in to ft. 12 Weight: 2.35 Casing height above land surface: in.. lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 9 ABS 1. Steel Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 9. Drilled holes 1. Continuous slot 5. Gauzed wrapped 7. Torch cut 11. None (open hole) 2. Louvered shutter 8. Saw cut 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 38 70 From to ft., From ft. ft. to ft. From to ft., From ft. ft. to GRAVEL PACK INTERVALS: 24 ft. 70 to ft., From From ft. ft. From ft. to ft., From ft to ft. **GROUT MATERIALS:** Other bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite 4 Grout Intervals: From ft. 24 ft., From ft. to ft. From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 5. Cess Pool 8. Sewage lagoon 14. Abandon water well 2 Sewer lines 12. Fertilizer storage 3. Watertight sewer line 9. Feed yard 6. Seepage pit South How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG From From To To LITHOLOGIC LOG 0 topsoil 3 18 clay 18 42 medium sand 42 70 grey shale

Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/7/17 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/9/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb