

1 LOCATION OF WELL: County: Sedgwick Fraction: NE 1/4 NE 1/4 NW 1/4 Section Number: 17 Township Number: T 29 S Range Number: R 2 E
 Distance and direction from nearest town or city street address of well if located within city? See Below.

2 WATER WELL OWNER: Dawn K. Gerlach
 RR#, St. Address, Box #: 19021 W. 87th SO
 City, State, ZIP Code: Vista KS 67149
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 50 ELEVATION: 8-23-91
 Depth(s) Groundwater Encountered 1. 20 ft. 2. 20 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 20 ft. after 1/2 hours pumping 30 gpm
 Est. Yield 20 gpm: Well water was 20 ft. after 1/2 hours pumping 30 gpm
 Bore Hole Diameter: 0 in. to 0 ft. and 0 in. to 0 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 50 ft. Dia. 2.60 in. to 160 ft. Dia. 160 ft. Dia. 160 ft.
 Casing height above land surface 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 160
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft. From 30 ft. to 50 ft. From 30 ft. to 50 ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 50 ft. From 30 ft. to 50 ft. From 30 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	top soil			
4	18	clay			
18	31	Med Sand			
31	50	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-23-91 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 38 This Water Well Record was completed on (mo/day/yr) 8-23-91
 under the business name of Werner Drilling Inc by (signature) Werner