

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NW 1/4 SE 1/4 SE 1/4	20	T 29 S	R 2 E/W
Distance and direction from nearest town or city street address of well if located within city?					
Approx. 2 miles west of Clearwater, KS					
2 WATER WELL OWNER: Vulcan Materials Co.					
RR#, St. Address, Box # : P.O. Box 12283			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, KS 67277			Application Number: n/a		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: unknown			
		Depth(s) Groundwater Encountered 1. 16 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 3/18/83			
		Pump test data: Well water was not ck'd ft. after hours pumping gpm			
		Est. Yield Unknown gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 38 ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well & Monitor			
Was a chemical/bacteriological sample submitted to Department? Yes NoXX; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued XX Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
Blank casing diameter 4 in. to 28 ft., Dia		7 Fiberglass		Threaded	
Casing height above land surface 12 in., weight 1.822 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From 28 ft. to 38 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 38 ft., From ft. to ft.					
ANNULAR FILL From 10 ft. to 16 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From 16 ft. to 20 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? Southwest		13 Insecticide storage 500		Industrial Water Wells	
How many feet? 500					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10	Topsoil & sandy brown clay			
10	30	Sand & gravel, very fine to fine, clean w/a few thin streaks of shale and clay			
30	38	Sand & gravel, fine, clean w/a couple thin streaks of clay			
38	E	Gray & blue shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/18/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185. This Water Well Record was completed on (mo/day/yr) 4/7/83 under the business name of CLARKE WELL & EQ., INC. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

9

I

2

2

E/W

SEC

20

NW 1/4 SE 1/4 SE 1/4

14