

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Sedgwick</u>		NE ¼ SE ¼ SE ¼		20		T 29 S		R 2 EW	
Distance and direction from nearest town or city street address of well if located within city?									
Approximately 2½ miles west and ½ mile north of Clearwater, Kansas									
2 WATER WELL OWNER: Vulcan Materials Company - Chemicals Division									
RR#, St. Address, Box # : P.O. Box 12283						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Wichita, Kansas 67277						Application Number: N/A			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 42 ft. ELEVATION: unknown							
		Depth(s) Groundwater Encountered 1. 29 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was not ch'd. ft. after hours pumping gpm							
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter .9 in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 4 in. to 29 ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface 36 in., weight 1.55 lbs./ft. Wall thickness or gauge No. 173									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 29 ft. to 39 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 20 ft. to 39 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage Industrial Brine Field									
Direction from well? How many feet? Is located in Industrial Brine Field									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	4	Topsoil, sandy							
4	18	Clay, brown, soft, sandy and fine sand							
18	30	Sand and Gravel, fine to very fine to medium							
30	33	Clay, black							
33	38	Sand and Gravel, fine to medium							
38	39	Shale, black							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-21-89 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 12-28-89									
under the business name of Clarke Well & Equipment, Inc. by (signature) <i>[Signature]</i>									