


NE SW SE

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: <u>Sedgewick</u> Distance and direction from nearest town or city street address of well if located within city? <u>322 Michelle Clearwater KANS</u>		Section Number <u>23</u>		Township Number T <u>29</u> S		Range Number R <u>2</u> <u>W</u>	
2 WATER WELL OWNER: <u>BILL BALLARD</u> RR#, St. Address, Box #: <u>322 Michelle</u> City, State, ZIP Code: <u>CLEARWATER KANS 67024</u>		Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>36</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>1.7</u> ft. 2. <u>1.4</u> ft. 3. <u>1.4</u> ft. WELL'S STATIC WATER LEVEL <u>1.4</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>36</u> ft. after <u>1.7</u> hours pumping <u>1.4</u> gpm Est. Yield <u>1.7</u> gpm: Well water was <u>36</u> ft. after <u>1.4</u> hours pumping <u>1.4</u> gpm Bore Hole Diameter <u>8</u> in. to <u>36</u> ft. and <u>1.4</u> in. to <u>1.4</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes <u>NO</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? <u>Yes</u> No					
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter <u>5</u> in. to <u>36</u> ft. Dia <u>160</u> lbs./ft. Wall thickness or gauge No. <u>214</u> Casing height above land surface <u>24</u> in., weight <u>160</u> lbs./ft. Wall thickness or gauge No. <u>214</u>		CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify)		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)					
SCREEN-PERFORATED INTERVALS: From <u>26</u> ft. to <u>36</u> ft. From <u>14</u> ft. to <u>36</u> ft. GRAVEL PACK INTERVALS: From <u>14</u> ft. to <u>36</u> ft. From <u>14</u> ft. to <u>36</u> ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>14</u> ft. to <u>4</u> ft. From <u>14</u> ft. to <u>4</u> ft. From <u>14</u> ft. to <u>4</u> ft. From <u>14</u> ft. to <u>4</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>EAST</u> How many feet? <u>15</u>							
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG					
0	4	SAND LOAM					
4	17	CLAY					
17	36	SAND					
36		SHALE					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-30-84</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>402</u> This Water Well Record was completed on (mo/day/yr) <u>7-30-84</u> under the business name of <u>M.E. MILLAN WATER WELL</u> by (signature) <u>John E. McMillan</u>							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							