


WATER WELL RECORD Form WWC-5 KSA 82a-1212					
LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		NE 1/4 NE 1/4 NE 1/4	2	T 29 S	R 21 E/W
Distance and direction from nearest town or city street address of well if located within city?					
3 east 1/4 north of Bucklin					
WATER WELL OWNER: Mrs. Austin		Pickrell Drilling		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box #: Bucklin, Ks.		Litwin Bldg. Suite 205		Application Number: T83-122	
City, State, ZIP Code:		Wichita, Ks. 67202			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 160 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 90 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 120 ft. below land surface measured on mo/day/yr 3-25-83			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield NA gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to 160 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes HTH No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
3 Wrought iron					
6 Asbestos-Cement					
7 Fiberglass					
9 Other (specify below)					
Blank casing diameter 5 in. to 140 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 258					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 140 ft. to 160 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 160 ft., From ft. to ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? west		How many feet? 80			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 5 Top soil					
5 97 01 Clay (light brown)					
97 12005 Sand					
120 15504 Sandy streaked clay					
155 160/7 Sand and gravel					
160 01 Hard yellow clay					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-25-83 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 4-23-83					
Under the business name of Rosencrantz-Bemis Ent by (signature) Lora Dodson					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

DP