


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ford	NW ¼ NE ¼ SE ¼	5	T 29 S	R 21 EW

Distance and direction from nearest town or city street address of well if located within city?

201 South Main, Bucklin, Kansas 67824

2 WATER WELL OWNER:	Bucklin Coop	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	201 South Main	Application Number:
City, State, ZIP Code :	Bucklin, Kansas 67824	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 100 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. DRY ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 7 7/8 in. to 100 ft. and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Vapor Extraction
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass	Threaded X
Blank casing diameter 2 in. to 95 ft., Dia			
Casing height above land surface -3 in., weight			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 95 ft. to 100 ft., From		
	From ft. to ft., From		
GRAVEL PACK INTERVALS:	From 93 ft. to 100 ft., From		
	From ft. to ft., From		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 91 ft. to 91 ft., From				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? west			How many feet? 30	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	CONCRETE & FILL SND			
1	5	DK BRN SLTY CLY			SVE 2
5	10	BRN SLTY CLY			
10	20	RED BRN SLTY CLY			
20	27	RED BRN CLY - SLTY - SDY			
27	37	RED BRN SLTY CLY			
37	40	RED BRN CLY - SLTY TO SDY			
40	50	RED BRN SLTY CLY			
50	72	BRN SLTY CLY			
72	90	RED BRN SLTY CLY			
90	95	INTD CLY & THIN SND			
95	100	VF SND, BRN, RD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-25-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 03-05-93 under the business name of GeoCore Services, Inc. by (signature) Doug Ray
