


1 LOCATION OF WATER WELL: County: Ford	Fraction NW ¼ NE ¼ SE ¼	Section Number 5	Township Number T 29 S	Range Number R 21 E W
--	----------------------------	----------------------------	---------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

201 South Main, Bucklin, Kansas 67824

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	Bucklin Coop 201 South Main Bucklin, Kansas 67824	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: Depth(s) Groundwater Encountered 1. NA ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: NA ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 7.7/8 in. to 100 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Vapor extraction Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X
---	--

5 TYPE OF BLANK CASING USED: 1 Steel (2) PVC Blank casing diameter: 2 in. to 95 ft., Dia. in. to ft. Casing height above land surface: -3 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40	3 RMP (SR) 4 ABS 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded: X
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter (3) Mill slot 4 Key punched	(7) PVC 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 95 ft. to 100 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 93 ft. to 100 ft., From ft. to ft. From ft. to ft., From ft. to ft.	

6 GROUT MATERIAL: (1) Neat cement 2 Cement grout (3) Bentonite 4 Other	Grout Intervals: From 0 ft. to 91 ft., From 91 ft. to 93 ft., From ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard	10 Livestock pens 14 Abandoned water well (11) Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? west How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8"	CONCRETE			
8"	2'	DK BRN ORG CLY			SVE3
2'	10'	DK MED BRN SLTY CLY			
10	20	RED BRN SLTY CLY			
20	30	RED BRN SLTY CLY, TR SND			
30	37	RED BRN SLTY CLY			
37	40	LT BRN SLTY CLY			
40	45	RED BRN SLTY CLY			
45	60	BRN SLTY CLY			
60	72	BRN SLTY TO SDY CLY			
72	91	RED BRN SLTY CLY			
91	100	VF TO F BRN SND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-26-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 03-05-93 under the business name of GeoCore Services, Inc. by (signature) <i>[Signature]</i>
--