

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ford	NW 1/4 NE 1/4 SE 1/4	5	T 29 S	R 21 E (W)

Distance and direction from nearest town or city street address of well if located within city?

201 South Main, Bucklin, Kansas 67824

2 WATER WELL OWNER:	Bucklin Coop	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	201 South Main	Application Number:
City, State, ZIP Code :	Bucklin, Kansas 67824	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 118 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. NA ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: APP104 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 10 in. to 120 ft. and in. to ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
(2) PVC 4 ABS 7 Fiberglass Threaded X	
Blank casing diameter in. to 93 ft. Dia in. to ft. Dia in. to ft.	
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No. Sch. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:	(7) PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot (3) Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 93 ft. to 118 ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From 90 ft. to 120 ft. From ft. to ft.	

6 GROUT MATERIAL:	(1) Neat cement 2 Cement grout (3) Bentonite 4 Other
Grout Intervals: From 88 ft. to 88 ft. From 90 ft. to ft. From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy (11) Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? west How many feet? 40	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	CONCRETE			
6"	10'	DK TO MED BRN CLY			OBW1
10'	25'	RED BRN SLTY CLY			
25	35	MED BRN SLTY CLY			
35	45	RED BRN SLTY CLY			
45	90	MED BRN SLTY CLY			
90	95	INTBEDD SND & CLY			
95	100	VF TO F BRN SND			
100	120	F TO C SND, F TO C GRVL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02-02-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 03-05-93 under the business name of GeoCore Services, Inc. by (signature) Doug Ray
--