

1] LOCATION OF WATER WELL: County: FORD		Fraction NW ¼ NE ¼ SE ¼	Section Number 5	Township Number T 29 S	Range Number R 21 W
Distance and direction from nearest town or city street address of well if located within city? Maple & Elm midway on west side Hwy MW-8					
2] WATER WELL OWNER: Bucklin Coop Exchange RR#, St. Address, Box #: 201 S. MAIN City, State, ZIP Code: Bucklin, KS			Board of Agriculture, Division of Water Resources Application Number: 99.48'		
3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4] DEPTH OF COMPLETED WELL: 113 ft.			
<p>A diagram showing four sections labeled NW, NE, SW, and SE separated by dashed lines. An 'x' is marked in the SE section.</p>		ELEVATION: 99.48' Depth(s) Groundwater Encountered 1. 102 ft. 2. .ft. 3. .ft. WELL'S STATIC WATER LEVEL 101.75 ft. below land surface measured on mo/day/yr 5/30/91 Pump test data: Well water was .ft. after .hours pumping gpm Est. Yield .gpm Well water was .ft. after .hours pumping gpm Bore Hole Diameter 6 in. to 113 ft., and .in. to .ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ⑩ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5] TYPE OF BLANK CASING USED:					
Blank casing diameter .in. to 93 ft., Dia .in. to .ft., Dia .in. to .ft. Casing height above land surface .in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 113 ft. to .ft., From .ft. to .ft. GRAVEL PACK INTERVALS: From 85 ft. to 113 ft., From .ft. to .ft.					
6] GROUT MATERIAL: 1 Neat cement ② Cement grout ③ Bentonite 4 Other Grout Intervals: From 82 ft. to 0 ft., From 82 ft. to 85 ft., From .ft. to .ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ③ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? West How many feet? 115'					
FROM		TO		LITHOLOGIC LOG	PLUGGING INTERVALS
D	113			Clay - bun, silty	
<div style="position: absolute; bottom: 10px; right: 10px; font-size: 2em; transform: rotate(-15deg); opacity: 0.5;">HIGHT VANCE</div>					
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/30/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 6/2/91 under the business name of Groundwater Technology, Inc. by (signature) Steven K. McIntire					