

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		NW 1/4 NE 1/4 SE 1/4	5	T 29 S	R 21 EW

Distance and direction from nearest town or city street address of well if located within city?

201 South Main, Bucklin, Kansas 67824

2 WATER WELL OWNER:		Bucklin Coop	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :		201 South Main	Application Number:
City, State, ZIP Code :		Bucklin, Kansas 67824	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 116.5 ft. ELEVATION:	
		Depth(s) Groundwater Encountered 1. NA ft. 2. ft. 3. ft.	
		WELL'S STATIC WATER LEVEL APP104 ft. below land surface measured on mo/day/yr	
		Pump test data: Well water was ft. after hours pumping gpm	
		Est. Yield gpm: Well water was ft. after hours pumping gpm	
		Bore Hole Diameter 10 in. to 120 ft., and in. to ft.	
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC 4 ABS		7 Fiberglass		Threaded X
Blank casing diameter 4 in. to 91.5 ft., Dia in. to ft., Dia in. to ft.				
Casing height above land surface 37 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement				
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)				
		12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes				
		7 Torch cut 10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 91.5 ft. to 116.5 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 87 ft. to 120 ft., From ft. to ft.				

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 87 ft., From 85 ft. to 87 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? northwest		How many feet? 160			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	DK BRN ORG CLY			MW10
6"	4'	DK BRN CLY			
4'	10'	MED BRN CLY			
10	20	RED BRN SLTY CLY			
20	30	MED BRN SLTY CLY			
30	60	RED BRN SLTY CLY			
60	80	LT BRN SLTY CLY			
80	92	RED BRN SLTY CLY			
92	100	VF TO F SND, BRN			
100	120	F TO C SND, F TO C GRVL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02-01-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 03-05-93 under the business name of GeoCore Services, Inc. by (signature) Doug Ray	
---	--