


WATER WELL RECORD Form WWC-5 KSA 82a-1212					
1 LOCATION OF WATER WELL: County: Ford		Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 14		
Distance and direction from nearest town or city street address of well if located within city? 1 mile South on highway 34 and 2 3/4 miles East of Bucklin, Ks.		Township Number T 29 21 S	Range Number R 21 29 E		
2 WATER WELL OWNER: Mrs. Hattie Neely		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : City, State, ZIP Code : Bucklin, Kansas 67834		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 240 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 138 ft. below land surface measured on mo/day/yr Feb. 16, 1982 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 35 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 240 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No. XXX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XXX No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 5 in. to 240 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 12 in., weight 200 psi lbs./ft. Wall thickness or gauge No. SDR 21		CASING JOINTS: Glued XX Clamped Welded Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN-PERFORATED INTERVALS: From 195 ft. to 195 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 240 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? South and East		How many feet? 120			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	Top soil & brown clay			
15	75	Brown clay			
75	105	Fine sand & brown clay layers			
105	135	Mixed sand			
135	225	Medium to coarse sand			
225	240	Medium to coarse sand & shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Feb. 17, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) March 8, 1982 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) <i>Sam R. Crick</i> INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					