| 1 LOCATION OF WATER WELL:<br>COUNTY: 029 FORD   | Fraction<br>SE 1/4 NE 1/4 NE   | ; Secti  | ion Number ;  | Township Num<br>T 29                              | ber :                        | Range Number<br>R <u>26</u> 21 W |
|---|--|--|---|---|------------------------------|----------------------------------|
| Distance and direction from ne 5 S. 3 1/2 W. OF MULLINVILLE,  | earest town or city stre<br>KS   | et address of well   | if located with   | in city?  |                              |                                  |
| RR#, St. Address, Box #: 32   |  |  | Board of Agric  | ulture, Divis                                     | ion of Wa                    | ter Resources                    |
| City, State, ZIP code : BU  | CKLIN, KS 67834-   |  | Application Nu  | mber:   |                              |                                  |
| 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  |  |  |   | <b>'0</b> ft. 2.                                  | ft.                          | 3.                               |
| / \   | ; WELL'S STATIC  | WATER LEVEL 170<br>o testdata: Well w  |   |   |                              |                                  |
| 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1   | Estimated Yiel   | ld gpm: Well   | water was   | ft. after   | hours                        | pumping                          |
| i W   | X¦ E ¦ Bore Hole Diam  | neter 2  | in. to 180 ft   | ., and i  | in. to                       | ft.                              |
| e :   | WELL WATER TO  | BE USED AS: 01 DOM   | ESTIC   |   |                              |                                  |
| , ,   |  | l/bacteriological s  | ample submitted   | to department                                     | t? <b>No ;</b><br>Water well | l disinfected?                   |
| 5 TYPE OF BLANK CASING USED: 01   | STEEL CA   | <br>Sing Joints: Thread  | <br>DED   |   |                              |                                  |
| 5 TYPE OF BLANK CASING USED: 01   | STEEL CA<br>in. to 180 ft.,<br>ace -30 in., weil<br>MATERIAL: NONE USED  | SING JOINTS: THREAD<br>Dia in. to<br>ght lbs/ft.   | <br>DED   |   |                              |                                  |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION   | STEEL CALL in. to 180 ft., ace -30 in., wei MATERIAL: NONE USED S ARE: 05 GAUZE WRA  | SING JOINTS: THREAD Dia in. to ght lbs/ft. P.  | oED ft., Dia Wall thickness   | in. to<br>or gauge No.                            |                              |                                  |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING   | in. to 180 ft., ace -30 in., wei MATERIAL: NONE USED S ARE: 05 GAUZE WRA  From 178 ft. From ft. From ft.                                     | SING JOINTS: THREAD<br>Dia in. to<br>ght lbs/ft.<br>P.   | ft., Dia ft., Dia Wall thickness  ft. to ft. to ft. to              | in. to<br>or gauge No.                            |                              |                                  |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  6 GROUT MATERIAL 03 BENTONI 6 Grout Intervals: From 2 What is the nearest source of                            | in. to 180 ft., ace -30 in., weil MATERIAL: NONE USED S ARE: 05 GAUZE WRA  From 178 ft. From ft. From ft. From ft.                           | SING JOINTS: THREAD Dia in. to ght lbs/ft.  P.  to 180 ft., From to ft., From to ft., From to ft., From to ft., From | oft., Dia Wall thickness  ft. to ft. to ft. to ft. to ft. to        | in. to<br>or gauge No<br>ft.<br>ft.<br>ft.<br>ft. | ft.<br>40                    |                                  |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING  SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: 6 GROUT MATERIAL 03 BENTON1: 6 Grout Intervals: From 2 What is the nearest source of Direction from well? SOUTH  | in. to 180 ft., ace -30 in., weil MATERIAL: NONE USED S ARE: 05 GAUZE WRA  From 178 ft. From ft. From ft. From ft.                           | SING JOINTS: THREAD Dia in. to ght lbs/ft.  P.  to 180 ft., From to ft., From to ft., From to ft., From to ft., From | oft., Dia Wall thickness  ft. to ft. to ft. to ft. to ft. to        | in. to<br>or gauge No<br>ft.<br>ft.<br>ft.<br>ft. | ft.<br>40                    | w many feet?                     |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  6 GROUT MATERIAL 03 BENTONI Grout Intervals: From 2 What is the nearest source of                              | in. to 180 ft., ace -30 in., weil MATERIAL: NONE USED S ARE: 05 GAUZE WRA  From 178 ft. From ft. From ft. From ft.                           | SING JOINTS: THREAD Dia in. to ght lbs/ft.  P.  to 180 ft., From to ft., From to ft., From to ft., From to ft., From | oft., Dia Wall thickness  ft. to ft. to ft. to ft. to ft. to        | in. to or gauge No.  ft. ft. ft. ft. ft.          | ft.<br>40                    | w many feet?                     |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  6 GROUT MATERIAL 03 BENTON1 6 Grout Intervals: From 2 What is the nearest source of Direction from well? SOUTH | in. to 180 ft., ace -30 in., wei MATERIAL: NONE USED S ARE: 05 GAUZE WRA  From 178 ft. From ft. From ft. From ft. From ft. From ft. From ft. | SING JOINTS: THREAD Dia in. to ght lbs/ft.  P.  to 180 ft., From to ft., From to ft., From to ft., From to ft., From | ft., Dia Wall thickness  m ft. to m ft. to m ft. to m ft. to ft. to | in. to or gauge No.  ft. ft. ft. ft. ft.          | ft.<br>40                    | w many feet?                     |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  6 GROUT MATERIAL 03 BENTON1 6 Grout Intervals: From 2 What is the nearest source of Direction from well? SOUTH | in. to 180 ft., ace -30 in., wei MATERIAL: NONE USED S ARE: 05 GAUZE WRA  From 178 ft. From ft. From ft. From ft. From ft. From ft. From ft. | SING JOINTS: THREAD Dia in. to ght lbs/ft.  P.  to 180 ft., From to ft., From to ft., From to ft., From to ft., From | ft., Dia Wall thickness  m ft. to m ft. to m ft. to m ft. to ft. to | in. to or gauge No.  ft. ft. ft. ft. ft.          | ft.<br>40                    | w many feet?                     |
| 5 TYPE OF BLANK CASING USED: 01 Blank casing diameter 2 Casing height above land surf TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENING  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTON1: Grout Intervals: From 2 What is the nearest source of Direction from well? SOUTH    | in. to 180 ft., ace -30 in., wei MATERIAL: NONE USED S ARE: 05 GAUZE WRA  From 178 ft. From ft. From ft. From ft. From ft. From ft. From ft. | SING JOINTS: THREAD Dia in. to ght lbs/ft.  P.  to 180 ft., From to ft., From to ft., From to ft., From to ft., From | ft., Dia Wall thickness  m ft. to m ft. to m ft. to m ft. to ft. to | in. to or gauge No.  ft. ft. ft. ft. ft.          | ft.<br>40                    | w many feet?                     |

completed on (mo/day/year) 8/20/92 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 224 This Water Well Record was completed on (ma/day/yr) 08/20/92
under the business name of CARL HAYSE WATER WELL SVC by (signature)