

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

| | | | | | | |
|--|--|---|--|----------------------------|--|-------------------------------|
| 1. Location of well: | | County FORD | Fraction NW 1/4 NE 1/4 NW 1/4 | Section number 3 | Township number T 29 S | Range number R 22 W |
| 2. Distance and direction from nearest town or city: 4 1/2 W. Bucklin Kans | | | 3. Owner of well: Omar Dankel R.R. or street: City, state, zip code: | | | |
| 4. Locate with "X" in section below: N W E S 1 Mile | | | Sketch map: 6. Bore hole dia. 8 3/4 in. Completion date 12-20-77 Well depth 170 ft. 7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary 8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input checked="" type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other 9. Casing: Material <input type="checkbox"/> Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 18 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 200 lbs./ft. Dia. 5 in. to 170 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 200 | | | |
| 5. Type and color of material | | | From | To | | |
| Top Soil | | | 0 | 2 | SurFlow Plastics | |
| LT BROWN Clay | | | 2 | 99 | Type RMP Dia. 5 | |
| Gravel | | | 99 | 100 | Slo gauge Length 20 | |
| LT BROWN Clay with 1" circles Streaks of Gravel | | | 100 | 122 | Set between 150 ft. and 170 ft. | |
| Gravel | | | 122 | 127 | Gravel pack? X Size range of material 8 X 5 | |
| Clay | | | 127 | 129 | 11. Static water level: mo./day/yr. | |
| Gravel 1/2 x 1 Tight | | | 129 | 154 | 128 ft. below land surface Date 12-21-77 | |
| Cream Colored Clay | | | 154 | 157 | 12. Pumping level below land surfaces: | |
| Gravel 1/2 to 1 | | | 157 | 167 | 128 ft. after 2 hrs. pumping 11 g.p.m. | |
| Clay Cream Colored | | | 167 | 170 | ft. after hrs. pumping g.p.m. | |
| | | | | | Estimated maximum yield 20 g.p.m. | |
| | | | | | 13. Water sample submitted: mo./day/yr. | |
| | | | | | Yes X No Date | |
| | | | | | 14. Well head completion: | |
| | | | | | Pitless adapter 18 Inches above grade | |
| | | | | | 15. Well grouted? YES | |
| | | | | | With: X Neat cement Bentonite Concrete | |
| | | | | | Depth: From 0 ft. to 10 ft. | |
| | | | | | 16. Nearest source of possible contamination: | |
| | | | | | ft. Direction Cattle Type | |
| | | | | | Well disinfected upon completion? Yes X No | |
| | | | | | 17. Pump: | |
| | | | | | Not installed | |
| | | | | | Manufacturer's name JFW Pump Co | |
| | | | | | Model number 7B412 HP 341 Volt 230 | |
| | | | | | Length of drop pipe 147 ft. capacity 10 g.p.m. | |
| | | | | | Type: | |
| | | | | | X Submersible Turbine | |
| | | | | | Jet Reciprocating | |
| | | | | | Centrifugal Other | |
| | | | | | (Use a second sheet if needed) | |
| 18. Elevation: | | 19. Remarks: | | | | |
| Topography: | | | | | | |
| <input type="checkbox"/> Hill | | | | | | |
| <input checked="" type="checkbox"/> Slope | | | | | | |
| <input checked="" type="checkbox"/> Upland | | | | | | |
| <input type="checkbox"/> Valley | | | | | | |
| | | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Carl Mayes Well Serv 224 Business name License No. Address 6003 So. Maple Greensburg Signed Carl Mayes Date 12-21-77 Authorized representative | | | | |