COUNTY:	029 FORD	WELL:	; SE	on 1/4 NW	1/4 NW	1/4	¦ Section ¦ 13		¦ Township ¦ T 29				
Distance 2 WEST OF					city street								
		Box # : F		R, HOME	R 51		i	Board of Agi	riculture, D	ivision	of Wa	ter Res	ources
City, Sta	te, ZIP o	code : I	KINGSDOWN	KS	67858-		1	Application	Number:		:		
				-	PTH OF COMPL pth(s) Groun					2.	ft.	3.	
\	X	; ;	: : :	: WELL	'S STATIC WA Pump t	TER LEVE estdata:	_ 155 ft Well wate	. below land er was	d surface me ft. after	asured (day/yr pumping	
5 1 1 2	1	1 1		-	mated Yield						hours	pumping	į
	·	i i	¦ E	; Bore	Hole Diamet	er	8.75 in	. to 225	ft., and	in.	to	ft.	
!	; ; - 511	; : SE		; WELL	WATER TO BE	USED AS	: 01 DOMES	TIC					
/ ;	* !	;	!	! If y	a chemical/b es, mo/day/y	acteriol r sample	ogical sam was submi	ple submitte tted	ed to depart	ment? No Wate		disinf	ected? \
Blank cas	LANK CAS	ING USED: (02 PVC 205 in.	to 2	CASIN 25 ft., Dia	G JOINTS	n. to	ft., Dia	in. t	0	ft.		
Blank cas Casing he TYPE OF S SCREEN OR	LANK CAS ing diame ight abov CREEN OR PERFORA	ING USED: (eter 2 ve land sur PERFORATION OPENIN	02 PVC 205 in. rface DN MATERII	to 2 12 in., 11: 07 08	CASIN 25 ft., Dia weight PVC SAW CUT	G JOINTS:	n. to bs/ft. Wa	ll thicknes	s or gauge N	e. 26	ft.		
Blank cas. Casing he TYPE OF SI SCREEN OR SCREEN PE	LANK CAS ing diame ight abov CREEN OR PERFORAT	ING USED: (eter 2 ve land sur PERFORATIO TION OPENIN	02 PVC 205 in. rface DN MATERII NGS ARE:	to 2 12 in., 12: 07 08	CASIN 25 ft., Dia weight PVC SAW CUT	G JOINTS:	n. to bs/ft. Wa t., From	ll thicknes	s or gauge N ft.	c. 26	ft.		
Blank cas. Casing he TYPE OF SI SCREEN OR SCREEN PE	LANK CAS ing diame ight abov CREEN OR PERFORAT	ING USED: (eter 2 ve land sur PERFORATION OPENIN	02 PVC 205 in. rface DN MATERII NGS ARE:	to 2 12 in., 12: 07 08	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to	16 JOINTS:	n. to bs/ft. Wa t., From t., From t., From	ll thicknes	s or gauge N ft. ft. ft.	o 26	ft.		
Blank cas Casing he TYPE OF SI SCREEN OR SCREEN PEI GRA GROUT MAT Grout Int	LANK CASSING diametric dight above CREEN OR PERFORATED VEL PACK ERIAL ervals:	ING USED: (eter 2 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS: 03 BENTON	02 PVC 205 in. rface DN MATERINGS ARE: :	to 2 12 in., AL: 07 08 From From From From 25 f	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From	ft. to ft. to ft. to	s or gauge N ft. ft. ft.	c. 26	ft.		
Blank cas. Casing he TYPE OF SI SCREEN OR SCREEN PE GRA GROUT MAT Grout Int. What is t	LANK CASING diametric dight above CREEN OR PERFORATED VEL PACK ERIAL ervals: he neare:	ING USED: (eter 2 ve land sur PERFORATIO TION OPENIN INTERVALS: INTERVALS: 03 BENTON From 4	02 PVC 205 in. rface DN MATERINGS ARE: :	to 2 12 in., AL: 07 08 From From From From 25 f	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From	ft. to ft. to ft. to	ft. ft. ft. ft.	c. 26	 	many f	eet?
Blank cas. Casing he TYPE OF SI SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t	LANK CAS: ing diame ight abov CREEN OR PERFORATED VEL PACK ERIAL ervals: he neare: from we:	ING USED: (eter 2 ve land sur PERFORATION OPENIN INTERVALS: INTERVALS: 03 BENTON: From 4 ve st source (11? N.W.	D2 PVC 205 in. rface : DN MATERIN NGS ARE: : ITE 4 ft. to of possib	to 2 12 in., AL: 07 08 From From From From 25 f	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From t., From	ft. to ft. to ft. to ft. to	ft. ft. ft. ft.	c. 26	t. Kow	many f	
Blank cas. Casing he TYPE OF SI SCREEN OR SCREEN PE GRA GROUT MAT Grout Int. What is t Direction FROM ;	LANK CAS ing diame ight abov CREEN OR PERFORATED VEL PACK ERIAL ervals: he neares from we:	ING USED: (eter 2 ve land sur PERFORATION OPENIN INTERVALS: INTERVALS: 03 BENTON From 4 st source (11? N.W.	D2 PVC 205 in. rface DN MATERINGS ARE: : : : : : : : : : : : : : : : : : :	to 2 12 in., AL: 07 08 From From From From From From	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From t., From	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	c. 26	t. Kow		
Blank cas. Casing he TYPE OF S: SCREEN OR SCREEN PE: GRA GROUT MAT Grout Int. What is t Direction FROM ; 1 ; 140 ; 190 ;	LANK CASING diametric diam	ING USED: (eter 2 ve land sur PERFORATION OPENIN INTERVALS: INTERVALS: O3 BENTON: From 4 st source (11? N.W. SILT & S. TAN CLAN TAN CLAN O5 SAND	D2 PVC 205 in. rface DN MATERINGS ARE: : : : : : : : : : : : SAND Y Y 05 SAND AND 17 61	to 2 12 in., 11: 07 08 From From From From From From Trom Trom Trom Trom	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From t., From	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	c. 26	t. Kow		
Blank cas. Casing he TYPE OF SI SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM : 1 : 140 :	LANK CASING diametric dight above CREEN OR PERFORATED VEL PACK ERIAL ervals: he neare: from we: TO 1 140 190	ING USED: (eter 2 ye land sur PERFORATION OPENIN INTERVALS: INTERVALS: 03 BENTON: From 4 st source (11? N.W.	D2 PVC 205 in. rface IN MATERIO NGS ARE: : : : : : : : : : : : : : : : : : :	to 2 12 in., 11: 07 08 From From From From From From Trom Trom Trom Trom	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From t., From	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	c. 26	t. Kow		
Blank cas. Casing he TYPE OF SI SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM : 1 : 140 : 190 : 218 :	LANK CASING diametric diam	ING USED: (eter 2 ye land sur PERFORATION OPENIN INTERVALS: INTERVALS: O3 BENTON: From 6 ye land can	D2 PVC 205 in. rface IN MATERIO NGS ARE: : : : : : : : : : : : : : : : : : :	to 2 12 in., 11: 07 08 From From From From From From Trom Trom Trom Trom	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From t., From	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	c. 26	t. Kow		
Blank cas Casing he TYPE OF SI SCREEN OR SCREEN PE GRAUT MAT Grout Int What is t Direction FROM :	LANK CASING diametric diam	ING USED: (eter 2 ye land sur PERFORATION OPENIN INTERVALS: INTERVALS: O3 BENTON: From 6 ye land can	D2 PVC 205 in. rface IN MATERIO NGS ARE: : : : : : : : : : : : : : : : : : :	to 2 12 in., 11: 07 08 From From From From From From Trom Trom Trom Trom	CASIN 25 ft., Dia weight PVC SAW CUT 205 ft. to ft. to 25 ft. to ft. to	225 ft	n. to bs/ft. Wa t., From t., From t., From t., From t., From	ft. to ft. to ft. to ft. to	ft. ft. ft. ft. ft.	c. 26	t. Kow		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 11/25/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 06/25/91 under the business name of CARL HAYSE WATER WELL SVC by (signature was completed on the business name of CARL HAYSE WATER WELL SVC