

1 LOCATION OF WATER WELL		Fraction <u>DCC</u>	Section Number <u>29</u>	Township Number <u>T 29 S</u>	Range Number <u>R 22 EW</u>
County: <u>Jord</u>		<u>SE 1/4 SE 1/4 SW 1/4</u>			
Distance and direction from nearest town or city? <u>3 S, 1/2 E of Kingdawn</u>			Street address of well if located within city?		
2 WATER WELL OWNER: <u>Pickrell Drilling</u>			<u>MT. JESUS NW</u>		
RR#, St. Address, Box #: <u>Return Bldg - Suite 205</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: <u>Wichita, KS 67202</u>			Application Number: <u>T80-291</u>		
3 DEPTH OF COMPLETED WELL: <u>208</u> ft. Bore Hole Diameter: <u>9</u> in. to <u>208</u> ft. and <u> </u> in. to <u> </u> ft.					
Well Water to be used as:					
1 Domestic		3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation		4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
Well's static water level: <u>114</u> ft. below land surface measured on <u>6</u> month <u>5</u> day <u>80</u> year		Pump Test Data: Well water was <u> </u> ft. after <u> </u> hours pumping <u> </u> gpm			
Est. Yield: <u>NA</u> gpm		Well water was <u> </u> ft. after <u> </u> hours pumping <u> </u> gpm			
4 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	Casing Joints: Glued <u> </u> Clamped <u> </u>
2 <u>PVC</u>		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u> </u>
Blank casing dia: <u>5</u> in. to <u>188</u> ft. Dia		7 Fiberglass	Threaded <u> </u>		
Casing height above land surface: <u>12</u> in., weight <u> </u> lbs./ft. Wall thickness or gauge No. <u>238</u>		TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
Screen or Perforation Openings Are:		5 Gauzed wrapped	6 Wire wrapped	9 Drilled holes	11 None (open hole)
1 Continuous slot		3 Mill slot	7 Torch cut	10 Other (specify)	
2 Louvered shutter		4 Key punched	6 Saw cut		
Screen-Perforation Dia: <u>5</u> in. to <u>208</u> ft. Dia		Screen-Perforated Intervals: From <u>188</u> ft. to <u>208</u> ft. From <u> </u> ft. to <u> </u> ft. From <u> </u> ft. to <u> </u> ft.			
Gravel Pack Intervals: From <u>10</u> ft. to <u>208</u> ft. From <u> </u> ft. to <u> </u> ft. From <u> </u> ft. to <u> </u> ft.		5 GROUT MATERIAL:			
1 <u>Neat cement</u>		2 Cement grout	3 Bentonite	4 Other	
Grouted Intervals: From <u>0</u> ft. to <u>10</u> ft. From <u> </u> ft. to <u> </u> ft. From <u> </u> ft. to <u> </u> ft.		What is the nearest source of possible contamination:			
1 Septic tank		4 Cess pool	7 Sewage lagoon	10 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Seepage pit	8 Feed yard	11 Fertilizer storage	15 Oil well/Gas well
3 Lateral lines		6 Pit privy	9 Livestock pens	12 Insecticide storage	16 Other (specify below)
Direction from well: <u>5</u> How many feet: <u>75</u> ? Water Well Disinfected? Yes <u>HTH</u> No <u> </u>		Was a chemical/bacteriological sample submitted to Department? Yes <u> </u> No <u>no</u> If yes, date sample was submitted <u> </u> month <u> </u> day <u> </u> year: Pump Installed? Yes <u> </u> No <u>no</u>			
If Yes: Pump Manufacturer's name <u> </u> Model No. <u> </u> HP <u> </u> Volts <u> </u>		Depth of Pump Intake <u> </u> ft. Pumps Capacity rated at <u> </u> gal./min.			
Type of pump:		1 Submersible	2 Turbine	3 Jet	4 Centrifugal
		5 Reciprocating	6 Other		
5 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on <u>6</u> month <u>5</u> day <u>80</u> year.					
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>134</u>					
This Water Well Record was completed on <u>6</u> month <u>24</u> day <u>80</u> year under the business name of <u>Rosenkrantz - Bemis</u> by (signature) <u>Lora Dodson</u>					
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG	
		0 2 Top soil		140 140 Clay	
		2 10 Brown clay		140 208 Sand & gravel	
		10 35 Tan clay			
		35 52 Tan & white clay			
		52 62 Hard tan & brown clay		B/Rock 208	
		62 63 Rock		114	
		63 91 Tan & white clay		94' at the	
		91 93 Rock			
		93 96 Rock white & brown clay		in g	
		96 118 White & brown clay			
118 140 Sand & gravel					
ELEVATION:				2463	

OFFICE USE ONLY

T

29

R

22

EW

SEC

29

SE 1/4

SE 1/4

SW 1/4

1/4