WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County Fraction | | Section num | | | Township number | Range number |
|--|---------------------------------------|-----------------|-------------|----------|--|---|-------------------------------------|
| 1. Location of well: | | | | | | | |
| 2 Distance and disc | Ford | NW1/4 SW 1/4 SE | T | <u></u> | .7 | T 29 s | R 23 W E/W |
| 2. Distance and direction from nearest town or city: 1 east, 2 north, 12 east and 2 north of Bloom, Ks. 3. Owner of well: R.R. or street: | | | | | Deonard weddie | | |
| Street address of well location if in city: City, state, zip code: | | | | | code: | Minneola, Kansas 67865 | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia 9 7/8 in. Completion date | |
| N | | | | | | Well depth 246 ft. | |
| † | | | | | | 7 Cable tool _X Rotary Driven Dug | |
| NW NE | | | | | | Hollow rod Jetted Bored Reverse rotary | |
| ₩ | | | | | | 8. Use: Domestic Public supply Industry Irrigation Air conditioning X_ Stock | |
| SW SE | | | | | | Lawn Oil field water Other | |
| | | | | | | 9. Casing: Material PVC Height: Above or below Threaded Welded X Surface 24 in. RMP PVC X Weight 2.8 lbs./ft. | |
| <u>†</u> | | | | | | | |
| 1 → 1 Mile | | | | | Dia. 5 in. to 246 ft. dep | oth Wall Thickness: inches or | |
| 5. Type and color of | material | | | From | То | Dia in. to ft. dep | |
| | | | | | - | 10. Screen: Manufacturer's | |
| Top soil | | | | 0 | 9 | Type PVC | Dia. 5 ^{††} |
| Sandy clay with rock streaks | | | | ۹ | 141 | Slot/geome | Length |
| | | | | | | ft. | andft. |
| Med. to lar. sand & gravel | | | | 141 | 182 | | ange of material 1/64-5/3 |
| Clay | | | | 185 | 203 | 11. Static water level: 148 ft. below land su | mo./day/yr. rface Date 3-24-78 |
| Med. to lar. sand & gravel with clay streaks 203 250 | | | | | 12. Pumping level below lan | | |
| Med. to lar. sand & gravel with clay streaks 203 | | | | | 250 | ft. after | hrs. pumping g.p.m. |
| | | | | | | Estimated maximum yield — | hrs. pumping g.p.m. 50g.p.m. |
| | | | | | | 13. Water sample submitted: | 9 · F · · · · |
| | | | | | | Yes X No | Date |
| | | | | | | 14. Well head completion: | 24 Inches above grade |
| | | | | | | Pitless adapter 15. Well grouted? Yes | |
| | | | | | | With: X Neat cement | Bentonite Concrete |
| 1 Ma. 11. 11 | | | | | | Depth: From ft. to | |
| | | | | b ,; | | 16. Nearest source of possible ft. 400 Direction | le contamination: W Type old wel |
| | | | | | | Well disinfected upon compl | etion? XX YesNo |
| | | | | | | 17. Pump: Transfer | |
| Market Contract | | | | | <u> </u> | Manufacturer's name CIISI Model number | tomers Windmill |
| and the state of the state of the state of | e e e e e e e e e e e e e e e e e e e | | | 1.0 | | | ft. capacity 3 g.p.m. |
| | | | 10.9 | - : : | | Туре: | Turking |
| | | | | <u> </u> | | Submersible Jet | Turbine Reciprocating |
| (Use a second sheet if needed) | | | | | | Centrifugal | X Other |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's | |
| | | | | | is true to the best of my known | ny jurisdiction and this report wledge and belief. | |
| Topography: Well was not plugged. | | | | | Friesen Windm | ill 252 | |
| Hill Slope | | | | | Business name Address Meade, Ka | nsas 67864 | |
| Upland | | | | | Signed Signed | Date # 2-78 | |
| XX_ Valley | | | | | | Anthorized res | |