ToCATION OF WATER WELL: Fraction NE ½ SE ½ SW ½ NW ½ NW ½ Township No. Range Number Street/Rural Address of Well Location; if funkown, distance & direction from nearest town or intersection: If at owner's address, check here If J/H Nor-th, 11/4 West of Kingsdown If a owner's address, check here If J/H Nor-th, 11/4 West of Kingsdown If a owner's address, check here If J/H Nor-th, 11/4 West of Kingsdown If a owner's address, check here If J/H Nor-th, 11/4 West of Kingsdown If a owner's address, check here If
Country: Ford
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here 13/4 Mor/h,1 1/4 West of Kingsdown Latitude: Latitude: Latitude: Latitude: Longitude: Longitu
form nearest town or intersection: if at owner's address, check here Latitude: (in decimal degrees)
13/4 North 1 1/4 West of Kingsdown
2
2 WATER WELL OWNER:
RR#, Street Address, Box #: 155 N. Market- Ste 700 City, State, ZIP Code Wichita, KS 67202 GPS unit, Make/Mode: Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: -3 m, 3-5 m, 5-15 m, >15
City, State, ZIP Code Wichita, KS 67202
Stainless Steel PVC Other (Specify Stainless Steel PVC Other (Specify Stainless Steel Stainless Steel PVC Other (Specify Stainless Steel Stainless Steel PVC Other (Specify Steel Stainless Steel Stainless Steel PVC Other (Specify Steel Stainless Steel Stainless Steel PVC Other (Specify Steel Stainless Steel Steel Stainless Steel Steel Stainless Steel Steel Steel Stainless Steel Steel Steel Stainless Steel Steel Steel Stainless Steel Steel Steel Steel Steel Stainless Steel Steel Steel Steel Steel Steel Stainless Steel Steel Steel Steel Steel Steel Steel Steel Steel Stainless Steel Steel Steel Steel Stainless Steel Steel Steel Steel Steel Stainless Steel Steel Steel Steel Stainless Steel Steel Steel Stainless Steel Steel Steel Stainless Steel Steel Steel Steel Stainless Steel Steel Steel Steel Steel Steel Stainless Steel
SECTION BOX: N
AN "X" IN SECTION BOX: SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 158 ft. below land surface measured on mo/day/yr. 1:5-13 Pump test data: Well water was ft. after hours pumping gpm EST. YIELD, NIA, gpm well water was ft. after hours pumping gpm BST. YIELD, NIA, gpm well water was ft. after hours pumping gpm gpm depth gpm depth depth
Depth(s) Groundwater Encountered 1
Pump test data: Well water was
Pump test data: Well water was
STYPE OF CASING USED: Steel PVC Other Source of Bases Steel Stee
Bore Hole Diameter 10 in. to 337 ft., and in. to ft. Well WATER TO BE USED AS:Public water supply Geothermal Injection well
WELL WATER TO BE USED AS: Public water supply Geothermal njection well
Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted. Yes No If yes, mo/day/yr sample was submitted to Department? Yes No If yes, mo/day/yr sample was submitted. Yes Oil field water well disinfected? Yes No Oil field water well disinfected? Yes No Oil field water well was a chemical/bacteriological sample submitted to Department? Yes No Oil field water supply Dewatering Other (Specify was a chemical/bacteriological sample submitted to Department? Yes Oil field water supply Dewatering Other (Specify was a chemical/bacteriological sample submitted to Department? Yes Oil field water supply Dewatering Other (Specify water was submitted to Department? Yes Oil field water supply Oil field water water water supply Oil field water water water supply Oil field water water water water water water supply Oil field water water water water water water water supply Oil field water water water water water water water water supply Oil field water w
Irrigation Industrial Domestic-lawn & garden Monitoring well Water well disinfected? Yes No STYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5 in. to .237 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface. 18 in., Weight SDR-26 lbs/ft., Wall thickness or gauge No. Type OF SCREEN OR PERFORATION MATERIAL: None used (open hole) SCREEN OR PERFORATION DENINGS ARE: Continuous slot Mill slot Court of the wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From .237 ft. to .197 ft. to ft. f
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
S
Water well disinfected? Yes No No No No No No No N
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5. in. to .237. ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface. 18. in., Weight SDR-26. lbs/ft., Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From. 237. ft. to 197. ft., From ft. to ft. From. ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From. 237. ft. to 20. ft., From ft. to ft. From. ft. to ft., From ft. to ft. GROUT MATERIAL: Neat cement Cement grout Grout Intervals: From ft. to ft., From ft. to ft. Grout Intervals: From ft. to ft., From Sewer lines Seep Seep pit Feedyard Full storage Abandoned water well None Direction from well Distance from well Distance from well None Distance from well 139
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5. in. to .237. ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface. 18. in., Weight SDR-26. lbs/ft., Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From. 237. ft. to 197. ft., From ft. to ft. From. ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From. 237. ft. to 20. ft., From ft. to ft. From. ft. to ft., From ft. to ft. GROUT MATERIAL: Neat cement Cement grout Grout Intervals: From ft. to ft., From ft. to ft. Grout Intervals: From ft. to ft., From Sewer lines Seep Seep pit Feedyard Full storage Abandoned water well None Direction from well Distance from well Distance from well None Distance from well 139
Casing diameter .5. in. to .237. ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface18. in., Weight SDR-26. lbs./ft., Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No. Type OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Sauze wrapped Torch cut Other (specify) SCREEN-PERFORATED INTERVALS: From 237. ft. to 197. ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 237. ft. to 20. ft., From ft. to ft. Fr
Steel Stainless Steel PVC Other (Specify)
Brass
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)
SCREEN-PERFORATED INTERVALS: From 237 ft. to 197 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 237 ft. to 20 ft., From ft. to ft. From ft. to ft., From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Grout Intervals: From ft. to ft., From ft. to ft. Grout Intervals: From ft. to ft., From ft. to ft. ft. o ft. What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Sewer lines Sewer lines Seepage pit Feedyard Frettilizer storage Oil well/gas well Watertight sewer lines Seepage pit Feedyard Frettilizer storage Oil well/gas well FROM TO LITHOLOGIC LOG FROM TO LITHOLOG (cont.) or PLUGGING INTERVALS 0 4 Top soil 4 139 Tan clay 139 156 Tan clay & caliche 156 180 Sand & gravel- med, tight 180 187 Tan clay 187 231 Sand & gravel- med, tight
From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 237 ft. to 20 ft., From ft. to ft. From ft. to 20 ft., From ft. to ft. GROUT MATERIAL: Neat cement Cement grout Grout Intervals: From ft. to ft. Grout Intervals: From ft. to ft. What is the nearest source of possible contamination: Septic tank Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well Direction from well Distance from well FROM TO LITHOLOGIC LOG FROM TO LITHOLOG (cont.) or PLUGGING INTERVALS O 4 Top soil 4 139 Tan clay 139 156 Tan clay & caliche 156 180 Sand & gravel- med, tight 187 231 Sand & gravel- med, tight
GRAVEL PACK INTERVALS: From
From ft. to ft.
GROUT MATERIAL: Neat cement Cement grout Cement grout Intervals: From ft. to ft., From 20 ft. to ft., From ft. to ft. What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Sewer lines Seepage pit Feedyard Fertilizer storage Direction from well Distance from well FROM TO LITHOLOGIC LOG FROM TO LITHOLOG (cont.) or PLUGGING INTERVALS 139
Grout Intervals: From ft. to ft., From .20 ft. to .0 ft., From .ft. to ft. What is the nearest source of possible contamination: Septic tank
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Sewer lines Seepage pit Feedyard Direction from well TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG Tan clay 139 156 Tan clay & caliche 180 187 Tan clay 187 231 Sand & gravel- med, tight Livestock pens Fredyard
Septic tank
Sewer lines Cesspool Sewage lagoon Fuel storage Oil well/gas well None Direction from well FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC NOT PLUGGING INTERVALS Tan clay 139
Watertight sewer lines Seepage pit Feedyard Distance from well Distance from well FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC NOT PLUGGING INTERVALS 139 Tan clay 139 Tan clay Caliche 156 180 Sand & gravel- med, tight 187 231 Sand & gravel- med, tight
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS 0 4 Top soil
0 4 Top soil 4 139 Tan clay 139 156 Tan clay & caliche 156 180 Sand & gravel- med, tight 180 187 Tan clay 187 231 Sand & gravel- med, tight
4 139 Tan clay 139 156 Tan clay & caliche 156 180 Sand & gravel- med, tight 180 187 Tan clay 187 231 Sand & gravel- med, tight
4 139 Tan clay 139 156 Tan clay & caliche 156 180 Sand & gravel- med, tight 180 187 Tan clay 187 231 Sand & gravel- med, tight
139 156 Tan clay & caliche 156 180 Sand & gravel- med, tight 180 187 Tan clay 187 231 Sand & gravel- med, tight
156 180 Sand & gravel- med, tight 180 187 Tan clay 187 231 Sand & gravel- med, tight
180 187 Tan clay 187 231 Sand & gravel- med, tight
187 231 Sand & gravel- med, tight
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged
under my jurisdiction and was completed on (mo/day/year) .1.5-13 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 2-13-13.
under the business name of Rosencrantz-Bemis by (signature)
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone, 785-296-5524. See done conv. to WATER, WELL OWNER, and retain one for your records. Lealude for of \$5.00 for each converted and 1. We shall be seen to be
Telephone 785-296-5524. Sen d one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy