			WWC-5		Division of Wat					
			ge in Well Use		esources App. l		Well ID			
		WATER WELL:	Fraction NW 1/4 NE 1/4 SE 1/4	1	Township Number Range Number R 29 S R 23 DE W					
County: Ford NW ¼ NE ¼ SE ¼ NE ¼ 3 T 29 S R 23 ☐ E ■ W 2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and										
Busines	s: Vincent	Oil Corp	Fust.		on from nearest town or intersection): If at owner's address, check here:					
Address	: 200 We	st Douglas, Ste 725			3/4 North, 3 West of Kingsdown					
Address		State: KS	7ID: 67202	1 3/4 11011	74 North, 5 West of Ringsdown					
	"X" IN	4 DEPTH OF COM			ft. 5 Latit					
	SECTION BOX: Depth(s) Groundwater Encountered: 1)									
	WELL'S STATIC WATER LEVEL:100					ontal Datum: U WGS e for Latitude/Longitude		83 LI NAD 27		
	below land surface, measured on (mo-day-y					19 GPS (unit make/model:)				
NW-	NE X	above land surface,	·yr)		(WAAS enabled? ☐ Yes ☐ No)					
		Pump test data: Well w			☐ Land Survey ☐ Topographic Map					
W	E after hours pumping					Online Mapper:				
SW-	SW SE after hours pumping				om Cara in					
		Estimated Yield:	gpm		6 Eleva	6 Elevation:ft. ☐ Ground Level ☐ TOC Source: ☐ Land Survey ☐ GPS ☐ Topographic Map				
	S Bore Hole Diameter:10 in. to			ft. and Source: Land Survey GP			GPS 110	pographic Map		
1 mile in. to ft.										
1. Domestic: 5. Public Water Supply: well ID										
☐ House		6. ☐ Dewatering								
☐ Lawn	& Garden	7. Aquifer Re		. 🗀 Ca	☐ Cased ☐ Uncased ☐ Geotechnical					
	Livestock 8. Monitoring: well ID									
2. ☐ Irrigat 3. ☐ Feedle	☐ Irrigation 9. Environmental Remediation: well ID					osed Loop	ital Vertic	cal		
4. Indust		☐ Air Sparge ☐ Recovery	☐ Injection	SAUACION	13. □ Ot	ther (specify):	ischarge []	inj. of water		
4. ☐ Industrial ☐ Recovery ☐ Injection 13. ☐ Other (specify):										
Water well disinfected? Yes □ No										
8 TYPE OF CASING USED: ☐ Steel PVC ☐ Other										
Casing diameter 5 in to 238 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 18 in Weight SDR-26 lbs./ft. Wall thickness or gauge No.										
Casing height above land surface										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)										
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ■ Saw Cut ☐ None (Open Hole)										
SCREEN-PERFORATED INTERVALS: From 238 ft. to 178 ft., From ft. to ft., From ft. to ft.										
GRAVEL PACK INTERVALS: From										
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From										
Nearest source of possible contamination:										
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage										
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well										
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well ☐ Other (Specify) None										
Direction from well? ft.										
10 FROM	TO	LITHOLOG		FROM		LITHO. LOG (cont.) o		INTERVALS		
0	2	Top soil				()				
2	27	Fine, silty clay					RECEIVE	ED		
27	143	Silty clay								
143	164	lay w/ sand & gravel streaks					EC 232	019		
	235	Sand & gravel- tight w/	light clay streaks					0.10		
235	238	Gray shale		Minter		BU	REAU OF V	NATER		
					Notes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged										
under my jurisdiction and was completed on (mo-day-year)										
Kansas Water Well Contractor's License No										
under the business name of Rosencrantz Remis. Ent Inc										
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.										
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015										