

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: FORD		NW ¼ NW ¼ SW ¼	16	T 29 S	R 24 E/W
Distance and direction from nearest town or city street address of well if located within city? 4½ North of Minneola, Kansas and 3 East.					
WATER WELL OWNER:		Buddy Piper Productions			
RR#, St. Address, Box # :		P.O. Box 171			
City, State, ZIP Code :		Tarzana, California 91356			
		Board of Agriculture, Division of Water Resources Application Number: ---			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 188 ft. ELEVATION: Slope			
		Depth(s) Groundwater Encountered 1 Not available ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL ... 105 ... ft. below land surface measured on mo/day/yr Feb. 7, 1985			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield k... 30 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter ... 9 7/8 in. to ... 188 ft., and in. to ft.			
		WELL WATER TO BE USED AS: XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No XX.....; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes XX No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . XX . Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Welded			
XXX PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Threaded			
Blank casing diameter ... 5 in. to ... 148 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface ... 12 in., weight ... 2.8 lbs./ft. Wall thickness or gauge No. ... 265					
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped XX Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From ... 148 ft. to ... 188 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ... 14 ft. to ... 188 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From ... 4 ft. to ... 14 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
XX Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? 70		How many feet? East			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	80	Clay			
80	100	Fine Sand			
100	120	Rock			
120	132	Med. to Lar. Sand			
132	140	Clay			
140	155	Med. to Lar. Sand & Gravel			
155	170	Gravel, Honey Cone			
170	188	Clay			
188	200	Black Shale			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Feb. 12, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) February 25, 1985 Under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature) INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					