

LOCATION OF WATER WELL:		WATER WELL RECORD		Form WWC-5		KSA 82a-1212	
County: Ford		Fraction: SE 1/4 NW 1/4 NW 1/4		Section Number: 33		Township Number: T 29 S 3	
Range Number: R 24 E 10		Distance and direction from nearest town or city street address of well if located within city?					
3 miles E. of Bloomington, Ind. 1/4 South							
WATER WELL OWNER: Jadd		Shelan #1-33					
RR#, St. Address, Box #: R 2994		Board of Agriculture, Division of Water Resources					
City, State, ZIP Code: Fairbairn, KS. 67901		Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 215 ft. ELEVATION: 215					
		Depth(s) Groundwater Encountered 1. 130 ft. 2. 170 ft. 3. 5/18/83					
		WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr 5/18/83					
		Pump test data: Well water was 170 ft. after 2 hours pumping 80 gpm					
		Est. Yield 80 gpm: Well water was 215 ft. after 2 hours pumping 80 gpm					
		Bore Hole Diameter 9 in. to 215 ft. and 2 in. to 215 ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
		Was a chemical/bacteriological sample submitted to Department? Yes No 8; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes 88 No					
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 8 Clamped					
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS		7 Fiberglass Threaded					
Blank casing diameter 9 in. to 0-215 ft. Dia 14 in. to 200 ft. Dia		Casing height above land surface 14 in. weight 200 lbs./ft. Wall thickness or gauge No. 0.265					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 230 ft. to 215 ft. From 125 ft. to 215 ft.					
GRAVEL PACK INTERVALS:		From 125 ft. to 215 ft. From 125 ft. to 215 ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 215 ft.					
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well		3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? East		How many feet? 200					
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG					
0 130 Overburden							
130 200 fine sand + clay							
200 215 Blue Clay							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/18/83 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 5/19/83							
under the business name of F & W Water Well Service by (signature) C. Ohlgenmaeller							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							