

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Ford</u>	<u>SW 1/4 SW 1/4 NW 1/4</u>	<u>9</u>	<u>T 29 S</u>	<u>R 25 E</u>

Distance and direction from nearest town or city street address of well if located within city?

From Minneola 5 miles north on 283 Hwy. 3 miles west, 1/2 mile south

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>HCR Box 198</u>	Application Number:
City, State, ZIP Code : <u>Minneola, KS 67865</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>275'</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>147'</u> ft. below land surface measured on mo/day/yr <u>11-16-92</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter <u>9 7/8"</u> in. to ft., and in. to ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
<u>1 Domestic</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes..... No. <u>X</u> If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
<u>2 PVC</u> 4 ABS 7 Fiberglass Threaded	
Blank casing diameter <u>5"</u> in. to <u>235'</u> ft., Dia in. to ft.	
Casing height above land surface <u>14"</u> in., weight lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:	8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>235'</u> ft. to <u>275'</u> ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From <u>24'</u> ft. to <u>275'</u> ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other
Grout Intervals: From <u>4'</u> ft. to <u>24'</u> ft., From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? <u>All Around</u>	How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil	280	300	white clay & slate
2	20	Brown clay			
20	25	fine sand (loose)			
25	40	Brown clay			
40	60	Brown clay & white rock layers			
60	76	fine sand & brown clay mixed			
76	84	white sand rock (loose)			
84	100	white rock layers & fine sand			
100	108	fine sand			
108	110	fine sand brown clay mixed			
110	145	med. sand			
145	156	med sand & brown clay layers			
156	174	med sand & thin white rock layers			
174	220	med. sand			
220	280	med. sand white clay layers			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , <u>(2) reconstructed</u> , or <u>(3) plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>11-16-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>533</u> This Water Well Record was completed on (mo/day/yr) <u>11-24-92</u> under the business name of <u>Jantzen Water Well Repair</u> by (signature) <u>[Signature]</u>
