

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: FORD	SW 1/4 SW 1/4 NW 1/4	13	T 29 S	R 25 EW

Distance and direction from nearest town or city street address of well if located within city?

5 1/2 North of Minneola, Kansas

2 WATER WELL OWNER:	Texaco Inc. c/o Chuck Dowlearn	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Rt. 2, Box 418	Application Number: ---
City, State, ZIP Code :	Minneola, Kansas 67865	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 220 ft. ELEVATION: Slope
	Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 165 ft. below land surface measured on mo/day/yr July 14, 1987
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 30 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 10 in. to 220 ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation XX Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes XX No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
XX2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 160 ft., Dia			Threaded
Casing height above land surface 15 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265			
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	XX8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:		From 160 ft. to 220 ft., From	ft. to ft.
GRAVEL PACK INTERVALS:		From 30 ft. to 220 ft., From	ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	XX Other Baroid Hole Plug
Grout Intervals:	From 0 ft. to 30 ft., From	ft. to ft.	ft. to ft.	ft. to ft.
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	XX16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	Oil Storage
Direction from well? Southwest		How many feet? 200		

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	106	Clay			
106	112	Clay and Fine Sand			
112	122	Clay			
122	127	Fine Sand			
127	135	Clay			
135	143	Clay and Fine Sand			
143	148	Caliche			
148	156	Clay			
156	160	Red Clay			
160	174	Med. to Lar. Sand & Gravel			
174	199	Caliche, Soft w/Sand			
199	201	Rock			
201	217	Clay and Large Gravel			
217	220	Red Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) July 21, 1987 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/yr) July 22, 1987
under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

0270000078-20