


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: FORD		SW 1/4 SE 1/4 NW 1/4	34	T 29 S	R 25 E
Distance and direction from nearest town or city street address of well if located within city? 3N 1 1/2 W 1/2 S OF MINNEOLA, KS					
2 WATER WELL OWNER: H-30 Drilling Company					
RR#, St. Address, Box # : 251 N. Water Suite 10			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, Kansas 67202			Lease: Watt A3 Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 130 ft. ELEVATION:			
N W E S 		Depth(s) Groundwater Encountered 1. 83 ft. 2. 83 ft. 3. 83 ft.			
		WELL'S STATIC WATER LEVEL 83 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was 35 gpm. Well water was 10 ft. after 130 ft. hours pumping 10 gpm			
		Bore Hole Diameter 10 in. to 130 ft. and 130 in. to 130 ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot (6) Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
(2) PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 5 in. to 73 ft. Dia 12 in. to 130 ft. Dia 12 in. to 130 ft.					
Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped (8) Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 73 ft. to 130 ft. From 73 ft. to 130 ft. From 73 ft. to 130 ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 130 ft. From 10 ft. to 130 ft. From 10 ft. to 130 ft.					
6 GROUT MATERIAL: 1 Neat cement (2) Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 130 ft. From 10 ft. to 130 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) NONE					
13 Insecticide storage					
Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG					
0 2 Soil					
2 48 Clay, tan					
48 83 Sand, fine to coarse and fine to med gravel, cemented					
83 98 Sand, cemented and caliche					
98 120 Dakota clays with some dakota sand					
120 130 Shale, red and blue					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9 FEB 84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 27 FEB 84 under the business name of Central Well & Pump Inc. by (signature) FD Honenmichl					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					