WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL County:	L: Fraction 1/4 SW 1/4 SE 1/4 SE 1/4	Section Number Township No. Range Number T 27 S R 25 DE 25 W
Street/Rural Address of Well Loca	tion; if unknown, distance & direction	Global Positioning System (GPS) information:
from nearest town or intersection:	If at owner's address, check here .	Latitude: (in decimal degrees)
Longitude: (in decimal degrees)		
2 Miles North & Mile East of Minneola 2 WATER WELL OWNER: Bob Denison		Elevation:
2 WATER WELL OWNER: \mathcal{B}_{i}	ob Denison	Collection Method:
RR#, Street Address, Box #: c/City, State, ZIP Code :	o Alex Stapelton	GPS unit (Make/Model:)
City, State, ZIP Code :	174 Yusca Rd 1-51	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
2 LOCATE WELL	1 in 4 rola, KS 6/863	Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m
3 LOCATE WELL WITH AN "X" IN 4 DEPTH	OF COMPLETED WELL	76 _{ft}
SECTION BOX: Depth(s) G	roundwater Encountered (1)	ft (2) ft (3) ft
N WELL'S S	TATIC WATER LEVEL92ft.	ft. (2) ft. (3) ft. below land surface measured on mo/day/yr
	Pump test data: Well water was	ft. after hours pumping gpm
EST. YIEL	D. 5.2gpm, Well water was	ft. after hours pumping gpm
W E Bore Hole Diameterft., andft.		
WELL WA	TER TO BE USED AS: Public wat	er supply Geothermal Injection well
Domestic		
was a chemical/bacteriological sample submitted to Department? Yes A No		
S If yes, mo/day/yr sample was submitted		
1 mile Water well disinfected?		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight Surface in., Weight Wall thickness or gauge No. 200 #		
Casing diameter		
Casing height above land surface		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
Steel Stainless Steel PVC Other (Specify)		
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.		
SCREEN-PERFORATED INTERVA	LS: From	b ft., From ft. to ft.
	From ft. to	ft., From ft. to ft.
GRAVEL PACK INTERVA	LS: From	ft., From ft. to ft.
From ft. to ft., From ft. to ft.		
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other		
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)		
Sewer lines		
☐ Watertight sewer lines ☐ See	page/pit Feedyard Fertilizer st	orage 🗷 Oil well/gas_well ,
Direction from well	Th Distance	from well 700
	DLOGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 & Topsoil		
8 55 Brown Cla	· y	
35 60 Caliche 80 65 Brown C/a	/	
60 65 Brown C/a	9/	
65 80 med to ms	d Coarse Sand	
80 107 Sandy Clay	nd some fund Streets	
10.7 119 Med Codys		
119 128 Caliche -/	Sand	
	Clay w/ Sandston & Layer	<i>f</i>
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, a reconstructed, or plugged		
under my jurisdiction and was completed on (mo/day/year)		
Kansas Water Well Contractor's License No		
under the business name of Southwest Windail by (signature)		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies		
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.		
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212		