WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	T _a	Γ		Т.		Topeka, Kansas 60020
1. Location of well:	II: Fraction Center		Section number		Township number Range number	
	Ford	1/4 1/4 N E1/4		14		T 29 S R 26 E
				er of well:		Gus Bartlett
Street address of well location if in city:				R. or street: ry, state, zip code:		1409 First Ave Dodge City, Kansas 67801
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 28 in. Completion date
, N						Well depth 195 ft. 11-16-77
	i i					7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary
NW DXE						8. Use: Domestic Public supply Industry
						X Irrigation Air conditioning Stock
sw	SE					LawnOil field waterOther 9. Casing: Material Steel Height: Above or below
<u> </u>					Threaded Welded X Surface 12 in.	
\$						RMPPVCWeightlbs./ft.
5. Type and color of material				From	То	Dia. 16 in. to 75 ft. depth Wall Thickness: inches or Dia in. to ft. depth gage No 188
,,,				-		10. Screen: Manufacturer's name W. A. Brown Ent.
Surface				0	3	Type Bridge Slot Dig. 16"
Clay				3	52	Slot/gauze 188 Length 491
				52	60	Set betweenft. andft.
Fine Sand & Clay				52	00	Gravel pack? X Size range of material 4 X 5/8
Fine to med. sand				60	70	11. Static water level: mo./day/yr
Med sand & gravel				70	114	12. Pumping level below land surfaces:
Clay				114	120	130 ft. after 2 hrs. pumping 1200 g.p.m.
Clay				11.4	120	Estimated maximum yield 2000 g.p.m.
Sand				120	124	13. Water sample submitted: mo./day/yr Yes No Date
Caliche & Clay layers				124	139	14. Well head completion:
Sand & Gravel				139	150	Pitless adapter Inches above grade
						15. Well grouted? <u>yes</u> With: Neat cement Bentonite X Concrete
Clay & Caliche & Sand layers				150	16 3	Depth: FromO ft. to10 ft.
Med. Fine sand				16 3	167	16. Nearest source of possible contamination: ft. 4-3/8mirectionS to Type Farm
Cemented sand & clay layers				167	174	Well disinfected upon completion? Yes X No
Fine sand & clay layers				174	18 9	17. Pump: Manufacturer's name Western Land Roll
Heavy brown clay				189	191	Model number 12 BH HP 100 Volts Length of drop pipe 180 ft. capacity 1200 p.m.
Shale					196	Type: Submersible X_ Turbine
				-/-		Jet Reciprocating
(Use a second sheet if needed)						Centrifugal Other
18. Elevation:	19. Remarks:					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report
Tanamak						is true to the best of my knowledge and belief.
Topography: Hill						Woofter Drilling Inc 343 Business name License No.
Slope						Address Hwy 56, Dodge City, KS
X_Upland						Signed Authorized representative