
100171011 07 11117	WATE		orm WWC-5	KSA 82a-				
LOCATION OF WATER WELL	1			tion Number		ip Number	Range Num	iber
ounty: Ford	SE 1/4		1/4	14	Т	29 S	R 26	- <b>(</b> W)
istance and direction from near			•					
	ely 4 miles east		1y 9 1/4	miles n	orth of	Fowler.		
WATER WELL OWNER: 0		E						
R#, St. Address, Box # : F					Board	of Agriculture, [	Division of Water F	Resource
	Fowler, Ks. 678					ation Number:		
LOCATE WELL'S LOCATION AN "X" IN SECTION BOX:		OMPLETED WELL2 water Encountered 1.						
		WATER LEVEL Appr						
	1 1	test data: Well water						
NW NE -	• = 1 1	5 gpm: Well water						
	1 1	eter. 9 . 7./8 in. to .				•		
w <del>                                    </del>			Public wate		B Air condition		Injection well	
w i i	4 5		Oil field wat			•	Other (Specify bel	love)
SW SE -	2 Irrigation	-					(Specify bei	
1 ! ! !		pacteriological sample su	_	-				
<u> </u>		bacteriological sample su	iomitted to De	-		-		was su
TYPE OF BLANK CASING U	mitted	C Mary also in a	0.0			fected? Yes		
		5 Wrought iron	8 Concre				I X Clamped	
	MP (SR)	6 Asbestos-Cement	· ·	specify below	,		ed	
2 PVC 4 A	=	7 Fiberglass					ded	
ank casing diameter 5.								
asing height above land surfac		.in., weight 2. <b>.</b> . 902						• • • • • •
YPE OF SCREEN OR PERFO			7 PV		10	Asbestos-ceme	nt .	
	tainless steel	5 Fiberglass		P (SR)	11	Other (specify)		
	alvanized steel	6 Concrete tile	9 ABS	5	12	None used (op	en hole)	
CREEN OR PERFORATION O	PENINGS ARE:	5 Gauzeo	wrapped		8 Saw cut		11 None (open i	hole)
1 Continuous slot	3 Mill slot	6 Wire w	rapped		9 Drilled ho	oles		
2 Louvered shutter	4 Key punched	7 Torch o	cut		10 Other (sp	ecify)		<i>.</i>
CREEN-PERFORATED INTER	VALS: From]	L70 ft. to	190	ft., From	1 200	) ft. to	220	.'f
	From	ft. to		ft., From	1 <i>.</i>	ft. te	). <i></i>	
GRAVEL PACK INTER	IVALS: From	· 25· · · · · ft. to	220	ft., From	1 . <i></i>	ft. to	)	f
	From	ft. to		ft., From	1	ft. to	)	f
		2 Cement grout						
rout Intervals: From5	5 ft. to 2.5	ft., From	ft. 1	io	ft., From	m	. ft. to	ff
hat is the nearest source of po	ossible contamination:			10 Livesto	ock pens	14 AI	andoned water w	/ell
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel s	torage	15 O	l well/Gas well	·
2 Sewer lines 5	5 Cess pool	8 Sewage lagoor		n 12 Fertilizer		er storage 16 Othe		w)
3 Watertight sewer lines	Seepage pit	9 Feedyard		13 Insecti	cide storage			
rection from well? East	•	•		How man	_	10'		
FROM TO	LITHOLOGIC I	LOG	FROM	TO		PLUGGING II	ITERVALS	
1 1 6			1					
	lee attached loc	<b>1</b>	1					
	See attached loo	<b>I</b>						
	See attached log	I						
	See attached loo	J						
	See attached log	J						
	See attached log	J						
	See attached log	j						
	See attached log							
	See attached log							
	See attached loo							
	See attached loo							
	See attached loo							
	See attached loc							
	See attached log							
	See attached log							
CONTRACTOR'S OR LANDO			s (1) construc	ated, (2) recor	nstructed, or	(3) plugged und	er my jurisdiction	and wa
CONTRACTOR'S OR LANDO	DWNER'S CERTIFICATION	ON: This water well was					er my jurisdiction	
	DWNER'S CERTIFICATION 17-17-90.	ON: This water well was		and this record	d is true to th	e best of my kno		
CONTRACTOR'S OR LANDO mpleted on (mo/day/year) ater Well Contractor's License	DWNER'S CERTIFICATION 17-17-90.	ON: This water well was	Il Record was	and this record	d is true to th n (mo/day/yr)	e best of my kno	wledge and belief	





## DRILLING & SUPPLY CO., INC.

3795 W. JONES AVE. 316/277-2389 FAX/277-0224

P.O. Box 639 GARDEN CITY, KANSAS 67846

CUSTOMER'S NAMEGailand Bartlett					DATE	July 17				
				x 39						
CITY &	STATE	Fo	wler, K	s. 67844		DRILLER _	Shelden			
COUNT	YFord	<u> </u>	_ QUART	ER SE SEC	TION14	_ TOWNSHIP _	_29 R	ANGE 26		
LOCAT	ION	10' n	orth we	st of old well						
		•					Hou	se well	locati	
	F	OOTAGE				STATIC WATER LEVEL: Approx. 90'				
%	From Pay		To	DESCRIPTION OF STRATA		Proposed Well Depth: 220				
	0		2	Top soil						
	2		26	_	clay					
	26		101		sticky					
	101		147		clay & some		sand stre	eaks		
	147		155	-	clay & some					
60	155	38	193	Sand fine to	medium coar	se small g	ravel			
	193		204	Brown sandy	clay & lime	rock ledge	s			
60	204	_16_	220	Sand fine to	medium coar	se small g	ravel			
	220		229	Brown sandy	clay & some	fine sand	streaks			
	229	·	233	Brown sandy	clay & lime	rock				
	233		262	Soap stone						
		ļ								
				1 -	= 220'					
	<del> </del>		<del> </del>		caps					
		<del> </del>			bags Hole Plu					
	<del> </del>			1 - 50 lb.	bag Hi-Tek					
	<del> </del>		<del> </del>							
		····	ļ <u>.</u>							
		<del> </del>		Donth	E # DVC 1	Perf	E" DVC	casing		
		<u> </u>		Depth 220-200	20'	Peri	5 PVC	Casing		
		1		200-190			10	\ t		
		<b></b>	<b> </b>	190-170	20'			,		
				170- 0			170	1		
					40'		180			
					-					
					10.1111					
									-	
	·									
			•							
1										