

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: FORD	SE 1/4 SW 1/4 SW 1/4	15	T 29 S	R 24 E

Distance and direction from nearest town or city street address of well if located within city?

8 miles north Fowler, KS

2 WATER WELL OWNER: LARRY Sturgeon	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: RR	Application Number:
City, State, ZIP Code: Fowler, KS. 67844	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 80 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr 10/1/83 Pump test data: Well water was N/A ft. after hours pumping gpm Est. Yield 20 gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to ft. and in. to ft. WELL WATER TO BE USED AS: <input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
AWC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to ft. Dia.			11 Other (specify)
Casing height above land surface 14 in., weight 250 lbs./ft. Wall thickness or gauge No. 250			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From 95 ft. to 125 ft.			
GRAVEL PACK INTERVALS:			
From 125 ft. to 20 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	B Bentonite	4 Other
Grout Intervals:	From 20 ft. to 0 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:				
1 Septic tank	Q Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? 90 ft.			How many feet? 100	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	TOP SOIL			
3	25	CLAY			
25	80	SAND			
80	125	GROVE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/1/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 161 This Water Well Record was completed on (mo/day/yr) 10/1/83 under the business name of Clagg Drilling by (signature) Larry Sturgeon
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

26

EW

SEC

15

SE 1/4

SW 1/4

SW 1/4