PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Tapeka Kansas 66620

						Topeka, Kansas 00020
	County	Ford Fraction NW 1/4 NW 1/4 SE1/4		Section number 21		Township number Range number
1. Location of well:	Ford					T 29 S R 26 E
8 N & 1 E of Fowler, Kansas R.R. or s Street address of well location if in city:				ner of well street:		Jr. NKX Wakeman RFD Fowler, Kansas 67844
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 28 in. Completion date Well depth 191 ft. 11-20-76
- NW NE E						7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary
						8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other
SW SE 1 1 1 5					9. Casing: Material Steel Height: Above or below Threaded WeldedX Surface lbs./ft. RMP PVC Weight lbs./ft.	
1 Mile → 1					T	Dia. 16in. to 0 ft. depth Wall Thickness; inches or Dia. 16in. to 80 ft. depth gage No. 188
5. Type and color of	material			From	То	10. Screen: Manufacturer's name
Surface				0	2	W. A. Brown Type Bridge Dia. 16
Clay				2	11	Slot/gauze
Caliche & Clay				11	56	ft. and ft. Gravel pack? X Size range of material 1/4 x 5/8
Sand & Gravel				56	103	11. Static water level: mo./day/yr.
Clay				103	114	12. Pumping level below land surfaces:
Sand & Gravel				114	124	186 ft. after 2 hrs. pumping 948 g.p.m. ft. after hrs. pumping g.p.m.
Caliche				124	139	Estimated maximum yield950g.p.m. 13. Water sample submitted:mo./day/yr.
Gray & Brown clay				139	143	Yes X No Date 14. Well head completion:
Hard brown rock				143	146	Pitless adapter 12 Inches above grade 15. Well grouted? X
Brown sand rock & sand layers				146	15 3	With: Neat cement _X Bentonite Concrete Depth: FromO ft. toO ft.
Gray Clay				15 3	155	16. Nearest source of possible contamination:
Sand rock				155	174	ft. 3/4 minimizer of the first state of the first s
Clay			174	181	17. Pump: Manufacturer's name Worthington	
Sand rock			181	184	Model number 5-12CH HP Volts Volts Length of drop pipe 177 ft. capacity 700g.p.m.	
Gray clay				184	191	Type: Submersible
Shale	(Use a second :	sheet if needed)		191	195	Jet Reciprocating Other 6
18. Elevation:	19. Remarks:					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report
Topography: Hill Slope X Upland					V	is true to the best of my knowledge and belief. Oofter Drilling Inc. 343 Business name Address Hwy 56, Dodge City, KS Signed Authorized representative