


1 LOCATION OF WATER WELL: County: <u>Ford</u>		Fraction NW 1/4 SW 1/4 SW 1/4		Section Number <u>29</u>	Township Number T <u>29</u> S	Range Number R <u>26</u> E/W
Distance and direction from nearest town or city street address of well if located within city? <u>From Dodge City - 17 Miles South, 9 Miles West, 850 Ft. North & 5,240 Ft. West</u>						
2 WATER WELL OWNER: <u>Bernita McKissick</u> RR#, St. Address, Box # : <u>600 Chestnut</u> City, State, ZIP Code : <u>Fowler, Kansas 67844</u> Board of Agriculture, Division of Water Resources Application Number: <u>118</u>						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>195</u> ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>70</u> ft. below land surface measured on mo/day/yr <u>4-30-83</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>26</u> in. to <u>195</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <u>2</u> Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>				
5 TYPE OF BLANK CASING USED: <u>1</u> Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> Blank casing diameter <u>16</u> in. to <u>110</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>12</u> in., weight <u>42.05</u> lbs./ft. Wall thickness or gauge No. <u>250</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement <u>1</u> Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass <u>4</u> Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot <u>3</u> Mill slot <u>6</u> Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>110</u> ft. to <u>195</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>10</u> ft. to <u>195</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement <u>2</u> Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>0</u> ft. to <u>10</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage <u>N/A</u> Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS See attached log						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-1-83</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>208</u> This Water Well Record was completed on (mo/day/yr) <u>6-28-83</u> under the business name of <u>Minter-Wilson Drilling Co., Inc.</u> by (signature) <u>Nora Keller</u>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

The Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

BERNITA Mc KISSICK
FORD COUNTY
1-12-83

LOCATION ; SW: 29-29-26
270' SOUTH OF OLD WELL
STATIC WATER LEVEL : 67

TEST # 2

0 4 01 TOP SOIL
4 40 04 BROWN SANDY CLAY
40 44 17 FINE TO MED SAND & GRAVEL (TIGHT)
44 50 04 BROWN SANDY CLAY
50 56 17 FINE TO MED SAND & GRAVEL
56 76 04 BROWN SANDY CLAY
76 80 09 FINE TO MED SAND (LOOSE)
80 131 12 FINE TO MED SAND & GRAVEL (LOOSE)
131 142 04 BROWN SANDY CLAY
142 157 17 FINE TO MED SAND & GRAVEL STREAKS OF CLAY (10%) LO
157 190 17 FINE TO MED SAND & GRAVEL (LOOSE)
190 200 04 BROWN SANDY CLAY
200 209 17 BROWN & BLUE CLAY
209 247 01 BLUE CLAY
247 260 04 BROWN & WHITE SANDY CLAY SMALL STREAKS OF WHITE ROCK
260 263 17 FINE TO MED SAND & GRAVEL (LOOSE)
263 286 04 BROWN SANDY CLAY & WHITE ROCK (15%) LOOSE
286 289 17 FINE TO MED SAND & GRAVEL (LOOSE)
289 305 04 BROWN SANDY CLAY
305 320 30 WHITE ROCK STREAKS OF CLAY (40%) (LOOSE)
320 335 09 FINE SAND WITH WHITE ROCK & BROWN SANDY CLAY (15%)
LOOSE
335 352 04 BROWN SANDY CLAY & FINE SAND
352 370 20 BROWN SANDY CLAY STREAKS OF BROWN ROCK (20%) (LOOSE)
370 375 01 BROWN YELLOW CLAY
375 380 19 SHALE