WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL:	Fraction 1/4 NE 1/4 BW/4 NE 1/4	Section Number Township No. Range Number T 29 S R 26 E	- 1117
County: Street/Rural Address of Well Location;	if unlimous distance & direction	Global Positioning System (GPS) information:	<u>n</u> w
from nearest town or intersection: If at		Latitude:	ees)
		Longitude: (in decimal degree	
Il Miles North o	A towlor	Elevation:	
2 WATER WELL OWNER: H L	K JLH	Datum: WGS 84, NAD 83, NAD 27	
2 WATER WELL OWNER: Hugh RR#, Street Address, Box #: P. 0	LOYFIELT	Collection Method: GPS unit (Make/Model:)
City, State, ZIP Code :	er KS 67844	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Surv	
		Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL	ϟ 7	
SECTION BOX: Depth(s) Groun	dwater Encountered (1)	ft. (2) ft. (3)	. ft.
SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
Pump	test data: Well water was	ft. after hours pumping g	,pm
W NW NE EST. YIELD	gpm. Well water was	ft., andin. toft.	pm
WELL WATER	R TO BE USED AS: Public wat	ter supply Geothermal Injection well	
Domestic	☐ Feedlot ☐ Oil field wat	ter supply Dewatering Other (Specify belo	ow)
☐ Irrigation	☐ Industrial ☐ Domestic-law	wn & garden Monitoring well	
		o Department? 🔲 Yes 🗶 No	
	/day/yr sample was submitted		
water wen dish	nfected? Yes No		
5 TYPE OF CASING USED: Steel PVC Other Other			
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in to ft Diameter in to ft Diameter in to ft			
Casing diameter			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
☐ Steel ☐ Stainless Steel ☐ Other (Specify)			
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:			
Continuous slot Mill slot			
Louvered shutter Key punched Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.			
SCREEN-PERFORATED INTERVALS:	From	ft., From ft. to	ft.
GRAVEL PACK INTERVALS:	From 20 ft to 14	ft., From ft. to ft. to	π.
From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other			
Grout Intervals: From			
What is the nearest source of possible containing Septic tank	amination: nes	pens	
☐ Sewer lines ☐ Cesspool	Sewage lagoon Fuel storage		
☐ Watertight sewer lines ☐ Seepage I			
Direction from well FROM TO LITHOLOG	GIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVA	AT C
O 2 Topsoil	ile Lod FROM	TO LITHO. LOG (COIII.) OF PLUGGING INTERVA	ALS
2 63 Tan Clay.			
63 75 Mrd Sand			
75 83 Clay W/ Coass	r Sand Stroks		
83 105 Fight Med	Sand		
105 145 tellow (lay y)	San Streets		
147 147 Plack Skale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ★ constructed, □ reconstructed, or □ plugged			
under my jurisdiction and was completed on (mo/day/year)			
Wansas Water Well Contractor's License No			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies			
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212			