

1 LOCATION OF WATER WELL:	Fraction <u>NW 1/4 N 1/4 E 1/4 NE 1/4</u>	Section Number <u>25</u>	Township Number <u>T 29 S</u>	Range Number <u>R 27 E 10</u>
---------------------------	---	--------------------------	-------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

11 E + 6 S of Manhattan

2 WATER WELL OWNER: <u>D.A. Bartlett</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>510 Maple</u>	Application Number:
City, State, ZIP Code: <u>Fowler, KS 67844</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>142</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 105 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 85 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 91 ft. after 1 hours pumping 15 gpm

Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 3/4 in. to 142 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
6 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	7 Lawn and garden only	12 Other (Specify below)
	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒ No

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>Yes</u> ☒ Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>5</u> in. to <u>100</u> ft. Dia			
Casing height above land surface <u>24</u> in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Gauzed wrapped	10 Asbestos-cement	
1 Steel	6 Wire wrapped	11 Other (specify)	
2 Brass	7 Torch cut	12 None used (open hole)	
3 Stainless steel	8 RMP (SR)		
4 Galvanized steel	9 ABS		
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	9 Saw cut	11 None (open hole)	
1 Continuous slot	10 Drilled holes		
2 Louvered shutter	10 Other (specify)		
4 Key punched			
SCREEN-PERFORATED INTERVALS: From <u>100</u> ft. to <u>140</u> ft.			
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>140</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>top</u> ft. to <u>20</u> ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	<u>Creek</u>		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well? <u>N</u>	How many feet? <u>70</u>			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Topsoil			
5	18	brown clay			
18	85	sand & gravel			
85	105	white clay			
105	116	gravel			
116	125	white clay			
125	142	sand & gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-26-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>101</u> This Water Well Record was completed on (mo/day/yr) <u>4-23-93</u> under the business name of <u>Bartlett Well Drilling, Inc.</u> by (signature) <u>Rubert J. Bartlett</u>
