

## WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number												
COUNTY: GRAY		SW 1/4 SE 1/4 SW 1/4	34	T 29 S	R 28 W												
Distance and direction from nearest town or city street address of well if located within city? ON GRAY & MEADE CO. LINE - 2 W WEST - ON NORTH SIDE OF ROAD																	
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources															
WELLER, ALICE		Application Number:															
RR#, St. Address, Box # : 15187 A ROAD																	
City, State, ZIP code : MONTEZUMA, KS 67867-																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 243 ELEVATION: 0															
<div style="display: flex; align-items: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); margin-right: 5px;">1 mile</div> <table border="1" style="border-collapse: collapse; text-align: center;"> <tr><td></td><td>NW</td><td>NE</td></tr> <tr><td>W</td><td></td><td></td></tr> <tr><td></td><td>SW</td><td>SE</td></tr> <tr><td></td><td>X</td><td></td></tr> </table> </div>			NW	NE	W				SW	SE		X		Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.			
			NW	NE													
		W															
			SW	SE													
	X																
WELL'S STATIC WATER LEVEL 105 ft. below land surface measured on mo/day/yr 11/08/95																	
Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm																	
Estimated Yield 50 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm																	
Bore Hole Diameter 9 in. to 243 ft., and in. to 0 ft.																	
WELL WATER TO BE USED AS: DOMESTIC																	
Was a chemical/bacteriological sample submitted to department? No ;																	
If yes, mo/day/yr sample was submitted Water well disinfected? Yes																	
5 TYPE OF BLANK CASING USED: PVC		CASING JOINTS: GLOUED															
Blank casing diameter 5 in. to 243 ft., Dia in. to 0 ft., Dia in. to 0 ft.																	
Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21																	
TYPE OF SCREEN OR PERFORATION MATERIAL: PVC																	
SCREEN OR PERFORATION OPENINGS ARE: SAW CUT																	
SCREEN PERFORATED INTERVALS:		From 220 ft. to 240 ft., From 0 ft. to 0 ft.															
GRAVEL PACK INTERVALS:		From 0 ft. to 0 ft., From 0 ft. to 0 ft.															
		From 25 ft. to 243 ft., From 0 ft. to 0 ft.															
		From 0 ft. to 0 ft., From 0 ft. to 0 ft.															
6 GROUT MATERIAL BENTONITE																	
Grout Intervals: From 0 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.																	
What is the nearest source of possible contamination: ABANDONED WELL																	
Direction from well? EAST		How many feet? 15															
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS												
0	40	TOPSOIL CLAY															
40	60	CALACHIE CLAY															
60	110	FINE - MED SAND - dry															
110	120	FINE SAND CLAY LAYERS															
120	150	FINE - MED SAND CLAY															
150	200	FINE - MED SAND SMALL GRAVEL															
200	260	FINE - MED SAND SMALL GRAVEL CLAY															
260	280	CLAY THIN ROCK LAYER															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed under my jurisdiction and was completed on (mo/day/year) 11/08/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 11/13/95 under the business name of JOE'S WELL SERVICE, INC. by (signature) <i>Joe's Well Service</i>																	