

Form WWC-5 KSA 82a-1212

KSA 82a-1212

LOCATION OF WATER WELL: County: Gray	Fraction NE 1/4 NE 1/4 NW 1/4	Section Number 11	Township Number T 29 S	Range Number R 28 E/W	
Distance and direction from nearest town or city street address of well if located within city? 5 East and 3 South of Montezuma, Kansas					
WATER WELL OWNER: RR#, St. Address, Box #: City, State, ZIP Code:	Broce Construction South Highway 283 Dodge City, Kansas 67801		Board of Agriculture, Division of Water Resources Application Number: ----		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 300 ft. ELEVATION: Slope. Depth(s) Groundwater Encountered 1. Not available 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 162 ft. below land surface measured on mo/day/yr June 3, 1986 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 10 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 7/8 in. to 300 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No XX If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No				
W	X	NE	SW	SE	
S					
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) XX 2 PVC 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued XX Clamped Welded Threaded.		
Blank casing diameter 5 in. to 260 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 15 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 XXXPVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)		
SCREEN-PERFORATED INTERVALS: From 260 ft. to 300 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 14 ft. to 300 ft., From ft. to ft.					
6 GROUT MATERIAL: XX Neat cement Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.	2 Cement grout 3 Bentonite	4 Other 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)		
What is the nearest source of possible contamination: NONE	How many feet?				
1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard			
Direction from well?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	37	Clay			
37	52	Caliche			
52	53	Crock Caliche			
53	113	Clay			
113	260	Black Shale			
260	300	Gray Sandstone			
300	360	Black Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 5, 1986 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) June 12, 1986
under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen, **PLEASE PRESS FIRMLY** and **PRINT** clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

05-85000058