



1 LOCATION OF WATER WELL:		Fraction 1/4	1/4	SW	1/4	Section Number 18	T 28 S	Range Number R 28 E
Distance and direction from nearest town or city street address of well if located within city?								
X 5 miles south of montezuma on east side apache dr. east side								
2 WATER WELL OWNER:		RODNEY KOEHN MONTEZUMA, KS.			Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL 140 ft. ELEVATION: Depth(s) Groundwater Encountered 140 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 140 ft. below land surface measured on mo/day/yr 1/29/85 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 7/8 in. to 140 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED:		1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped		
		<input checked="" type="checkbox"/> PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded		
		Blank casing diameter 5 in. to 97 ft., Dia		7 Fiberglass	Threaded			
		Casing height above land surface 12 in., weight 200		lbs./ft. Wall thickness or gauge No.				
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement			
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)			
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	12 None used (open hole)			
SCREEN-PERFORATED INTERVALS: From 97 ft. to 140 ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 50 ft. to 140 ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other			
Grout Intervals: From 4 ft. to 25 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well			
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
13 Insecticide storage								
Direction from well? north How many feet? 100								
FROM	TO	LITHOLOGIC LOG			FROM	TO	LITHOLOGIC LOG	
0	8	TOP SOIL						
8	30	BROWN CALY						
30	35	FINE TO MED SAND						
35	42	BROWN SANDY CLAY						
42	47	FINE TO MED SAND						
47	60	BROWN SANDY CLAY						
60	100	FINE TO MED SAND						
100	120	BROWN SANBY CLAY						
120	135	FINE TO MED SAND AND GRAVEL						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/6/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 172 This Water Well Record was completed on (mo/day/yr) 6/85 under the business name of JONAGAN DRILLING CO. by (signature) 								
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.								