


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Gray	Fraction SE 1/4 NW 1/4 SE 1/4	Section number 13	Township number T 29 S	Range number R 29 W
2. Distance and direction from nearest town or city: 5 south, 1/2 west, 1/8 north of Street address of well location if in city: Montezuma.			3. Owner of well: Gerald Dirks R.R. or street: Montezuma, Ks. 67867 City, state, zip code:		
4. Locate with "X" in section below: <div style="text-align: center;">N 1 Mile W 1 Mile E S</div>		Sketch map: 		6. Bore hole dia. 26 in. Completion date 4-15-77 Well depth 176 ft.	
5. Type and color of material		From		7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
				9. Casing: Material steel Height: Above surface Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 177 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 250 hpc	
				10. Screen: Manufacturer's name Johnson Type galv. Dia. 16" Slot/gage 10 ft. Length 10 ft. Set between 140-150 ft. and 156-166 ft. Perf: 110-140 ft. and 150-156, 166-176 Gravel pack? yes Size range of material 5" down	
				11. Static water level: 84 ft. below land surface Date 3-2-77 mo./day/yr.	
				12. Pumping level below land surfaces: 108 ft. after 2 hrs. pumping 900 g.p.m. 129 ft. after 4 hrs. pumping 1475 g.p.m. Estimated maximum yield 1475 g.p.m.	
				13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/> mo./day/yr.	
				14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade	
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
				16. Nearest source of possible contamination: N/A ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Goulds - US Pump Model number 12 JHC HP 100 Volts <input type="checkbox"/> Length of drop pipe 160 ft. capacity 1200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other					
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drill. Co. 208 Business name License No. Address Box A Garden City, Ks. Signed [Signature] Date 6-10-77 Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

*The
Professionals*

MINTER-WILSON DRILLING CO.
INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

GERALD BIRKS
GRAY COUNTY
12-20-76

Location: SE 13-29-29 500 Ft. north of #1
Static Water Level- 85'

Test #2

0	3	Top soil
3	81	Brown clay
81	150	Fine to med. sand and gravel
150	156	Brown clay
156	166	Fine to med. sand and gravel
166	187	Brown clay
187	196	Brown and yellow clay
196	200	Shale

T.D. 176'