


SW SW NE (DRL)

Form WWC-5

Division of Water Resources; App. No.

WATER WELL RECORD

1 LOCATION OF WATER WELL: County: <u>Greer</u>		Fraction <u>NE⁴ SW¹ SE¹ SW¹</u>	Section Number <u>21</u>	Township Number <u>T 29 S</u>	Range Number <u>R 29 E</u>		
Distance and direction from nearest town or city street address of well if located within city? <u>6 S + 3 1/2 W from Montezuma</u>		Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: <u>37° 30.901'</u> Longitude: <u>100° 29.856'</u> Elevation: <u>2661</u> Datum: _____ Data Collection Method: _____					
2 WATER WELL OWNER: RR#, St. Address, Box # : <u>35405 10 Road</u> City, State, ZIP Code : <u>Montezuma, KS 67867</u>							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <u>280</u> ft.					
Depth(s) Groundwater Encountered (1)..... ft. (2)..... ft. (3)..... ft. WELL'S STATIC WATER LEVEL <u>171</u> ft. below land surface measured on mo/day/yr. <u>5-12-08</u>							
Pump test data: Well water was <u>171</u> ft. after <u>1</u> hours pumping <u>30</u> gpm Est. Yield <u>50</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/ys Sample was submitted..... Water well disinfected? Yes No							
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile 10 Other (specify below) CASING JOINTS: Glued Clamped..... ② PVC 4 ABS 6 Asbestos-Cement 9 Welded..... Blank casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.							
Casing height above land surface <u>24</u> in., Weight lbs./ft. Wall thickness or guage No. <u>20.0</u>							
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass ② PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ③ Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From <u>240</u> ft. to <u>280</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>280</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ② Bentonite 4 Other							
Grout Intervals: From <u>top</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage ② Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well							
Direction from well? <u>NE</u> How many feet? <u>1500</u>							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
<u>0</u>	<u>8</u>	<u>top soil</u>					
<u>8</u>	<u>30</u>	<u>clayey</u>					
<u>30</u>	<u>100</u>	<u>brown clay</u>					
<u>100</u>	<u>160</u>	<u>Sandy brown clay</u>					
<u>160</u>	<u>280</u>	<u>sand & gravel w streaks of clay</u>					