


1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 NW 1/4 SW 1/4	Section Number 9	Township Number T 29 S	Range Number R 3W E/W
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

8500 S. 279th W. Viola, Kansas

2 WATER WELL OWNER: BURFORD, Phillip	Board of Agriculture, Division of Water Resource
3 WELL ADDRESS, BOX #: 8500 S. 279th W.	Application Number:
4 CITY, STATE, ZIP CODE: Viola, Kansas	

1 WELL'S LOCATION WITH SECTION BOX: 	4 DEPTH OF COMPLETED WELL 30 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 10 ft. BELOW LAND SURFACE MEASURED ON 11/13/1995 Pump test data: Well water was 11 ft. after 11 hours pumping 11 gpm Est. Yield 11 gpm: Well water was 11 ft. after 11 hours pumping 11 gpm Bore Hole Diameter 12 in. to 30 ft. and 11 in. to 11 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X ; If yes, mo/day/yr sample was submitted 11/13/1995 Water Well Disinfected? Yes X No
--	--

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing Diameter 5 in. to 24 in. Dia 2.35 lbs. / ft. Casing height above land surface 12 in. weight 2.35 lbs. / ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 2 Corrugated shutter 4 Key punched 6 Wire wrapped 7 Torch cut SCREEN PERFORATION INTERVALS: from 24 ft. to 30 ft. From 24 ft. to 30 ft. GRAVEL PACK INTERVALS: from 24 ft. to 30 ft. From 24 ft. to 30 ft.	8 Concrete tile CASING JOINTS: Glued X Clamped 9 Other (Specify below) Welded SDR-26 Threaded Wall thickness or gauge No. .214 7 PVC 10 Asbestos-cement 8 RMP (SR) 11 other (specify) 9 ABS 12 None used (open hole) 8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)
---	--

6 CEMENT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Gravel intervals: From 4 ft. to 24 ft. From 4 ft. to 24 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Power lines 5 Cess pool 8 Sewage lagoon 3 Water right sewer lines 6 Seepage pit 9 Feedyard 10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent
--

Direction from well?		How many feet?	
FROM	TO	LITHOLOGIC LOG	PLUGGING INTERVALS
0	10	fine sand	
10	19	medium sand	
19	20	clay	
20	30	medium sand	

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/13/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/15/95 Under the business name of Harp Well & Pump Service, Inc. by (signature)

Jane Frederick