

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: NW 1/4 NW 1/4 NW 1/4 Section Number: 3 Township Number: 29 Range Number: 3 EW: 3

Distance and direction from nearest town or city street address of well if located within city? 26201 W. 71st S.

2 WATER WELL OWNER: Caro Construction Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 527 N. Walnut Application Number:
City, State, ZIP Code: Wichita, KS 67203

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 12-7-98
Depth(s) Groundwater Encountered: 1 ft. 2. 20 ft. 3. 36 ft.
WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 12-7-98
Pump test data: Well water was 20 ft. after 11 hours pumping 36 gpm
Est. Yield 20 gpm: Well water was 11 ft. after 36 hours pumping 36 gpm
Bore Hole Diameter: 11 in. to 36 ft. and 36 in. to 36 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted 12-7-98
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
Blank casing diameter 6 in. to 20 ft., Dia. 2.40 in. to 36 ft., Dia. 160psi
Casing height above land surface: 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 160psi
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 160psi
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 160psi
SCREEN-PERFORATED INTERVALS: From 20 ft. to 36 ft. From 20 ft. to 36 ft.
GRAVEL PACK INTERVALS: From 20 ft. to 36 ft. From 20 ft. to 36 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other open field
Grout Intervals: From 3 ft. to 20 ft. From 20 ft. to 36 ft. From 36 ft. to 36 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) open field
Direction from well? open field How many feet? open field

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	16	clay			
16	30	sand			
30	36	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-7-98 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 12-31-98
under the business name of Weninger Drilling Inc by (signature) Michelle Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-6545. Send one to WATER WELL OWNER and retain one for your records.