

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SE 1/4 SE 1/4 NE 1/4		Section Number 2	Township Number T 29 S	Range Number R 3W 1/2W
Distance and direction from nearest town or city street address of well if located within city? 3 West of Clonmel, 1/2 South of 71st on the West Side of Road on 231st West. Viola, Kansas						
2 WATER WELL OWNER: Virgil Pauly RR#, St. Address, Box # : 23700 West 79th So. City, State, ZIP Code : Viola, Kansas Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 23 ft.				
		Depth(s) Groundwater Encountered 1. 23 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 12-1-82 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
		5 TYPE OF BLANK CASING USED:				
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded				
		Blank casing diameter 5 in. to 30 ft. Dia. Cer-Mac Styrene SDR-26 in. to ft. Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203				
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 14 ft. to 50 ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 40" ft. to 14 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination: Septic system not installed as yet 14 Abandoned water well						
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent						
Direction from well? How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
0	3	Topsoil				
3	28	Clay				
28	49	Medium Sand				
49	50	Gray Shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-1-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 3-28-83 under the business name of Harp Well & Pump Service, Inc. by (signature) M. Arnold						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

3

EWI

SEC

7

SE 1/4

SE 1/4

SE 1/4

NE 1/4