

1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 SW 1/4 Section Number 11 Township Number T 29 S Range Number R 3 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? 3 miles North and 1/4 miles E of Viola KS.

2 WATER WELL OWNER: David Palmer
 RR#, St. Address, Box #: 11308 Valley Hi Drive
 City, State, ZIP Code: Wichita KS 67209
 Board of Agriculture, Division of Water Resources
 Application Number: 38

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: 18 ft.

Depth(s) Groundwater Encountered 18 ft. 2. 18 ft. 3. 18 ft.
 WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 18 ft. after 18 hours pumping 18 gpm
 Est. Yield 18 gpm: Well water was 18 ft. after 18 hours pumping 18 gpm
 Bore Hole Diameter 18 in. to 18 ft. and 18 in. to 18 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
☒ 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes 18 No 18; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes 18 No 18

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 18 Clamped 18
☒ 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 18
☒ 2 PVC 4 ABS 7 Fiberglass Threaded 18
 Blank casing diameter 18 in. to 18 ft. Dia 18 in. to 18 ft. Dia 18 in. to 18 ft.
 Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. 18

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
☒ 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 18
☐ 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
☒ 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
☐ 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 18

SCREEN-PERFORATED INTERVALS: From 18 ft. to 18 ft. From 18 ft. to 18 ft.
 GRAVEL PACK INTERVALS: From 18 ft. to 18 ft. From 18 ft. to 18 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 18
 Grout intervals: From 18 ft. to 18 ft. From 18 ft. to 18 ft. From 18 ft. to 18 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
☒ 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
☐ 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
☐ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? East How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			<u>0</u>	<u>3</u>	<u>top soil</u>
			<u>3</u>	<u>18</u>	<u>Cement grout</u>
			<u>18</u>	<u>38</u>	<u>gravel</u>

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-23-94 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 2-24-94
 under the business name of Weninger Drilling Inc. by (signature) Susan Weninger