


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NW 1/4 NW 1/4 SW 1/4	Section Number 13	Township Number T 29 S	Range Number R 3 E
Distance and direction from nearest town or city street address of well if located within city? 2 N 2 E 1/2 N OF VIOLA, KS					
2 WATER WELL OWNER: Brandt Drilling Co. RR#, St. Address, Box # : Suit 1104 Douglas Bldg. City, State, ZIP Code : Wichita, Kansas 67202			Clausen #1 Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 5 ft. below land surface measured on mo/day/yr 31 March 82 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 25 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 26 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 11 ft. to 26 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 10 ft. to 26 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage NONE Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	2	Sandy top soil			
2	14	Sand, fine to coarse and fine to coarse gravel			
14	26	Shale, blue			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 31 March 82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 5 July 82 under the business name of Central Well & Pump Inc. by (signature) <i>[Signature]</i> INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

29

R

3

EW

SEC.

13

1/4

1/4

1/4

1/4