

1 LOCATION OF WATER WELL:

County: Sedgwick

Fraction

NW ¼ NE ¼ SW ¼

23

Section Number

Township Number

Range Number

Distance and direction from nearest town or city street address of well if located within city?

12N, 12E, Viola

2 WATER WELL OWNER:

RR#, St. Address, Box #

City, State, ZIP Code

Don Casher

Box 323

Viola, KS. 67149

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N

W

E

S

4 DEPTH OF COMPLETED WELL:

90 ft. ELEVATION:

Depth(s) Groundwater Encountered

1. 50 ft. 2. 80 ft. 3. ft.

WELL'S STATIC WATER LEVEL

40 ft. below land surface measured on mo/day/yr 6-2-90

Pump test data:

Well water was

ft. after

hours pumping

gpm

Est. Yield

gpm

Well water was

ft. after

hours pumping

gpm

Bore Hole Diameter

10 in. to 90 ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply

8 Air conditioning

11 Injection well

1 Domestic

3 Feedlot

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

2 Irrigation

4 Industrial

7 Lawn and garden only

10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

1 Steel

3 RMP (SR)

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

2 PVC

4 ABS

6 Asbestos-Cement

9 Other (specify below)

Welded

Blank casing diameter

5 in. to 50 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface

18 in., weight lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS:

From 50 ft. to 90 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS:

From 30 ft. to 90 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other Barbed - Hole Plug

Grout Intervals:

From 0 ft. to 30 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

How many feet? 400

Direction from well? SE

FROM

TO

LITHOLOGIC LOG

FROM

TO

PLUGGING INTERVALS

0

2

Sand

2

9

Clay

9

90

Blue-Gray Shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:

This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-2-90 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 395 This Water Well Record was completed on (mo/day/yr) 6-2-90

under the business name of Craig Roberts Co. by (signature) Craig Roberts

INSTRUCTIONS:

Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

4.