


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SW 1/4 Section Number 35 Township Number T 29 S Range Number R 3 E/W
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city: 1.50 1/2 E Viola KS.

2 WATER WELL OWNER: JERRY Smith
 RR#, St. Address, Box #: RHT BX 44
 City, State, ZIP Code: Conway Spgs KS 67031
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 1-3-90
 Depth(s) Groundwater Encountered 1. 17 ft. 2. 15 ft. 3. 12 ft.
 WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 15 ft. after 12 hours pumping 20 gpm
 Est. Yield 25 gpm Well water was 15 ft. after 12 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 50 ft. and 50 in. to 50 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☐ 1 Steel ☒ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 9 Other (specify below)
☐ 2 PVC ☐ 4 ABS ☐ 7 Fiberglass
 Blank casing diameter 5 in. to 18 ft. Dia 1.59 in. to 1.59 ft. Dia 1.59 in. to 1.59 ft. Dia 1.59 in. to 1.59 ft. Dia
 Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No SAR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 8 RMP (SR) ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 6 Wire wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 18 ft. to 50 ft. From 17 ft. to 50 ft.
 GRAVEL PACK INTERVALS: From 17 ft. to 50 ft. From 17 ft. to 50 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 17 ft. From 17 ft. to 50 ft. From 17 ft. to 50 ft. From 17 ft. to 50 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☒ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? North How many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>TOP 50</u>			
<u>2</u>	<u>12</u>	<u>CLAY</u>			
<u>12</u>	<u>50</u>	<u>SHALE</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-3-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 1-3-90 under the business name of Wenger Dully by (signature) [Signature]