·	tion 1/4 SE 1/4 SW 1/4		† T 29 S	Range Number
Distance and direction from nearest APPROX. 4.25 MILES NORTH AND 5.75 M		of well if located wit	hin city?	
WATER WELL OWNER: SUBLETTE RR#, St. Address, Box # : BOX 917	FEEDERS	Board of Agri	culture, Division	of Water Resources
City, State, ZIP code : SUBLETTE	, KS 67877-	Application M	lumber: 40,376	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	; 4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Enc			0 ft. 3. 0 f
1 1 1 1 1	WELL'S STATIC WATER LEVEL Pump testdata:	245 ft. below land Well water was (		
NW    NE	· ·	: Well water was (	) ft. after 0	hours pumping 0 g
W	E : Bore Hole Diameter	17.5 in. to 649 ft	., and in.	to 0 ft.
; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	WELL WATER TO BE USED AS:	03 FEEDLOT		;
/ X	Was a chemical/bacteriolog			
TYPE OF BLANK CASING USED: 01 STEEL	: 	WELDED		
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE	n. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL	to Oft., Dia		
TYPE OF BLANK CASING USED: 01 STEEN Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE	n. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL : 03 MILL SLOT	to Oft., Dia s/ft. Wall thickness	or gauge No2	
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE	1. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL : 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft.	to 0 ft., Dia s/ft. Wall thickness ., From 605 ft. to	or gauge No2 645 ft. 0 ft. 0 ft.	
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:	1. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL : 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft.	to 0 ft., Dia s/ft. Wall thickness  ., From 605 ft. to ., From 0 ft. to	or gauge No2 645 ft. 0 ft. 0 ft. 0 ft.	50 
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATE SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. t	12 in., weight 22 lbs RIAL: 01 STEEL: 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.	to 0 ft., Dia s/ft. Wall thickness  , From 605 ft. to	or gauge No2 645 ft. 0 ft. 0 ft.	50 
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. t. What is the nearest source of poss	12 in., weight 22 lbs RIAL: 01 STEEL: 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.	to 0 ft., Dia s/ft. Wall thickness  , From 605 ft. to	or gauge No2 645 ft. 0 ft. 0 ft. 0 ft.	50 
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of poss Direction from well? LOCAL AREA  FROM ; TO ; 0 ; 2 ; 01 CLAY	12 in., weight 22 lbs RIAL: 01 STEEL  03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.  10 25 ft., From 0 ft. to the contamination: WATER WELL  LITHOLOGIC LOG	to 0 ft., Dia s/ft. Wall thickness  , From 605 ft. to	or gauge No2  645 ft. 0 ft. 0 ft. 0 ft.	50 
Clark casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERIAL OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of poss Direction from well? LOCAL AREA  FROM : TO :  0 : 2 : 01 CLAY 2 : 54 : 04 SANDY CLAY 54 : 69 : 07 FINE SAND 0	12 in., weight 22 lbs RIAL: 01 STEEL  03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.  12 in., weight 22 lbs RF of the state of th	. to 0 ft., Dia 5/ft. Wall thickness ., From 605 ft. to ., From 0 ft. to	or gauge No2  645 ft. 0 ft. 0 ft. 0 ft.	ft.  How many feet?
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. t. What is the nearest source of poss Direction from well? LOCAL AREA  FROM : TO :  0 : 2 : 01 CLAY 2 : 54 : 04 SANDY CLAY	n. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.  10 25 ft., From 0 ft. to 11 ITHOLOGIC LOG 131 CALICHE 07 FINE SAND 15 MEDIUM SAND 15 GRAVEL 15 CRS GRAVEL	. to 0 ft., Dia 5/ft. Wall thickness ., From 605 ft. to ., From 0 ft. to	or gauge No2  645 ft. 0 ft. 0 ft. 0 ft.	ft.  How many feet?
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of poss Direction from well? LOCAL AREA  FROM : TO :  0 : 2 : 01 CLAY 2 : 54 : 04 SANDY CLAY 54 : 69 : 07 FINE SAND 0 69 : 109 : 05 SAND 13 FIN 109 : 112 : 04 SANDY CLAY 112 : 161 : 05 SAND 14 MED	n. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.  c 25 ft., From 0 ft. to dible contamination: WATER WELL  LITHOLOGIC LOG 31 CALICHE 07 FINE SAND B MEDIUM SAND E GRAVEL 15 CRS GRAVEL 07 FINE SAND GRAVEL 01 CLAY	. to 0 ft., Dia 5/ft. Wall thickness ., From 605 ft. to ., From 0 ft. to	or gauge No2  645 ft. 0 ft. 0 ft. 0 ft.	ft.  How many feet?
Blank casing diameter 8.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE From 5 ft. to What is the nearest source of poss Direction from well? LOCAL AREA  FROM : TO :  0 : 2 : 01 CLAY 2 : 54 : 04 SANDY CLAY 54 : 69 : 07 FINE SAND 0 69 : 109 : 05 SAND 13 FIN 109 : 112 : 04 SANDY CLAY 112 : 161 : 05 SAND 14 MED 161 : 246 : 05 SAND 13 FIN	n. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.  c 25 ft., From 0 ft. to dible contamination: WATER WELL  LITHOLOGIC LOG 31 CALICHE 07 FINE SAND B MEDIUM SAND E GRAVEL 15 CRS GRAVEL 07 FINE SAND GRAVEL 01 CLAY	. to 0 ft., Dia 5/ft. Wall thickness ., From 605 ft. to ., From 0 ft. to	or gauge No2  645 ft. 0 ft. 0 ft. 0 ft.	ft.  How many feet?
Blank casing diameter B.625 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From 5 ft. t What is the nearest source of poss Direction from well? LOCAL AREA  FROM : TO :  0 : 2 : 01 CLAY 2 : 54 : 04 SANDY CLAY 54 : 69 : 07 FINE SAND 0 69 : 109 : 05 SAND 13 FIN 109 : 112 : 04 SANDY CLAY 112 : 161 : 05 SAND 14 MED	o. to 649 ft., Dia in. 12 in., weight 22 lbs RIAL: 01 STEEL 03 MILL SLOT  From 330 ft. to 430 ft. From 475 ft. to 515 ft. From 25 ft. to 649 ft. From 0 ft. to 0 ft.  o 25 ft., From 0 ft. to ible contamination: WATER WELL  LITHOLOGIC LOG 31 CALICHE 07 FINE SAND B MEDIUM SAND E GRAVEL 15 CRS GRAVEL 07 FINE SAND GRAVEL 01 CLAY E GRAVEL 15 CRS GRAVEL	. to 0 ft., Dia 5/ft. Wall thickness ., From 605 ft. to ., From 0 ft. to	or gauge No2  645 ft. 0 ft. 0 ft. 0 ft.	ft.  How many feet?

completed on (mo/day/year) 05/19/92 and this record is true to the best of my knowledge and belief. Kansas: Water Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 06/09/92 under the business name of HENKLE DRILLING & SUPPLY

COUNTY:	041 HASK	R WELL:   Fraction (ELL   NE 1/4 SE 1/4 S	; s sw 1/4 ; o	ection Number 5		; Range Number ; R 31 W			
2 WATER W	WATER WELL OWNER: SUBLETTE FEEDERS  RR#, St. Address, Box #: BOX 917  Board of Agriculture, Division of Water Resources								
City, S	City, State, ZIP code : SUBLETTE, KS 67877- Application Number: 40,376								
FROM 310 317 324	T0 317 324 429 474 519 533 556 585 603 646 677								

'7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 05/19/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 06/09/92

under the business name of HENKLE DRILLING & SUPPLY

by (signature)

A. Pkule